

R+M motor control easywash365+



The choice of perfection



Optional operation with 2 pressure switches or 1 flow switch or without control function.



Sheet steel wall housing: RAL7035 powder-coated.

Delayed Total-Stop time for the motor: 30 seconds

Prepared: for remote on-off.

In case of inactivity: The control (with flow switch or pressure switches) is switched off after 15 minutes.

easywash365+

The easywash365+ motor control for professional use

- For the operation of motors with 4 - 7.5 kW power at 400 VAC, 50 Hz
- Dimensions H x W x D: 380 x 380 x 210 mm, IP 65, equipped with:
 - Supply: 400VAC, 50Hz, 3Ph / N / PE with main switch (cam switch) 25A
 - Control voltage conditioning 24VDC, 2.5A with backup fuse 2A
 - Motor outlet with power contactor 7.5kW and wide-range motor protection switch 8-32A
 - LOGO small control unit
 - 1 operating hours counter (IP 65) and 2 command and signaling devices in the door



Mounting: The fastening straps on the back are also rotatable by 90°.



Protection class: IP 65

Contactless: Activation of the power contactor to protect the small control unit.

Motor control easywash365+



Motor control for the operation of motors with 4 - 7.5 kW power at 400 VAC, 50 Hz, IP 65. RAL 7035. H x W x D 380 x 380 x 210 mm. Supply: 400VAC, 50Hz, 3Ph / N / PE with main switch (cam switch) 25A. Control voltage conditioning 24VDC, 2.5A with backup fuse 2A. Motor outlet with power contactor 7.5kW and wide-range motor protection switch 8-32A. LOGO small control unit. 1 operating hours counter (IP 65) and 2 command and signaling devices built into the door

R+M Nr.	Weight
920 001 380	14 kg