

## Removable screw connections

Male thread : male thread



Stainless steel

AG : AG
1/2" : 1/2"
3/4" : 3/4"

R+M Nr.	P
574 812 009	max. 150 bar 67
574 834 009	max. 150 bar 73

## Quick screw couplings ST-740 and nipples ST-741

Quick screw couplings ST-740 and nipples ST-741



M24 F : M.  
Max. 700 bar / 150 °C



M24 F : M.  
Max. 700 bar / 150 °C



M : M24 M.  
Max. 700 bar / 150 °C



M24 M : M24 M.  
Max. 700 bar / 150 °C

⊙
3/8"
1/2"
M24

R+M Nr.
200 740 501
200 740 503

R+M Nr.
200 740 601

R+M Nr.
200 741 501
200 741 503

R+M Nr.
200 741 600



M24 F : F.  
Max. 700 bar / 150 °C



M24 F : F.  
Max. 700 bar / 150 °C



F : M24 M.  
Max. 700 bar / 150 °C

⊙
1/4"
3/8"
M16x1

R+M Nr.
200 740 504
200 740 502
200 740 506

R+M Nr.
200 740 604
200 740 602

R+M Nr.
200 741 504
200 741 502

### Seals



O-ring - ST-740

R+M Nr.
050 000 408



O-ring - ST-741

R+M Nr.
050 001 000



Back ring - ST-740

R+M Nr.
050 000 407

Symbols IG female thread AG male thread ⇄ length I height ⊙ thread ⊗ diameter TYP type P pressure