

## Quick screw couplings ST-740 and nipples ST-741

### Quick screw couplings ST-740 and nipples ST-741



M24 F : M.  
Max. 700 bar / 150 °C



M24 F : M.  
Max. 700 bar / 150 °C



M : M24 M.  
Max. 700 bar / 150 °C



M24 M : M24 M.  
Max. 700 bar / 150 °C

⊙
3/8"
1/2"
M24

<b>R+M Nr.</b>
200 740 501
200 740 503

<b>R+M Nr.</b>
200 740 601

<b>R+M Nr.</b>
200 741 501
200 741 503

<b>R+M Nr.</b>
200 741 600



M24 F : F.  
Max. 700 bar / 150 °C



M24 F : F.  
Max. 700 bar / 150 °C



F : M24 M.  
Max. 700 bar / 150 °C

⊙
1/4"
3/8"

<b>R+M Nr.</b>
200 740 504
200 740 502

<b>R+M Nr.</b>
200 740 604
200 740 602

<b>R+M Nr.</b>
200 741 504
200 741 502

### Seals



O-ring - ST-740

<b>R+M Nr.</b>
050 000 408



O-ring - ST-741

<b>R+M Nr.</b>
050 001 000



Back ring - ST-740

<b>R+M Nr.</b>
050 000 407

Symbols female thread male thread length height thread diameter type