

Handverschraubungen

Handverschraubung : Außengewinde



Standard M22 : AG. Schwarz.
Max. 400 bar / 150 °C



Standard M21 : AG. Grau.
Max. 400 bar / 150 °C



Kurz M22 : AG. Schwarz.
Max. 400 bar / 150 °C

AG
1/4"
3/8"
1/2"
M16
M18
M21
M22

R+M Nr.	i
561 40	49 mm
561 60	46 mm
561 66	50 mm
561 80	51 mm
561 90	47 mm
561 98	49 mm
561 95	60 mm

R+M Nr.	i
564 20	44 mm
564 40	45 mm
564 50	43 mm
564 62	49 mm
564 60	60 mm

R+M Nr.	i
560 30	28 mm



Kurz M21 : AG. Grau.
Max. 400 bar / 150 °C



Kurz M22 : AG. Edelstahl.
Max. 400 bar / 150 °C



M22 : AG. Edelstahl.
Max. 500 bar


AG
1/4"
3/8"

R+M Nr.	i
563 20	27 mm


R+M Nr.	i
560 39	28 mm

R+M Nr.	i
561 49	48 mm
561 69	45 mm

Handverschraubung : Handverschraubung



HV M22 : HV M22.
Max. 400 bar / 150 °C



HV M22 : HV M21.
Max. 400 bar / 150 °C

⊙

R+M Nr.	i
561 96	50 mm

R+M Nr.	i
561 97	50 mm