

Quick screw couplings

Quick screw coupling : female thread



Standard M22 : F. Black.
Max. 400 bar / 150 °C


R+M Nr.	I
561 20	45 mm
561 30	45 mm
561 50	45 mm
561 65	45 mm

IG
1/8"
1/4"
3/8"
1/2"



Standard M21: F. Grey.
Max. 400 bar / 150 °C

R+M Nr.	I
564 00	42 mm
564 10	41 mm
564 30	41 mm



Standard 1/2" : F. Blue.
Max. 400 bar / 150 °C

R+M Nr.	I
561 10	43 mm



Short M22 : F. Black.
Max. 400 bar / 150 °C

R+M Nr.	I
560 10	31 mm
560 20	28 mm

IG
1/8"
1/4"
3/8"



M22 : F. Stainless steel.
Max. 500 bar

R+M Nr.	I
561 39	45 mm
561 59	45 mm

Seals



O-ring. 10x2.2. Viton

R+M Nr.	VPE
790 24	1
790 241 00	100



Back ring

R+M Nr.	VPE
050 001 440	1
787 001 100	100



O-ring. 10x2. Perbunan

R+M Nr.	VPE
790 10	1
790 100	100



O-ring. 10x2. Viton

R+M Nr.	VPE
790 20	1
790 201 00	100



O-ring. 10x2.2. Perbunan

R+M Nr.	VPE
790 25	1
790 251 00	100

Symbols thread female thread male thread height packing unit