

Quick screw nipples

Male thread : female thread



M22 M : F. Brass. Max. 400 bar

⊙	
1/8"	
1/4"	
3/8"	
1/2"	
M16	
M18	
M22	

R+M Nr.	i
565 10	29
565 20	29
565 40	29
565 65	29
565 90 *	34
565 66	33



M21 M : F. Brass. Max. 400 bar

R+M Nr.	i
567 10	30
567 20	29
567 40	29
567 60 *	30



1/2" M : F. Brass. Max. 400 bar

R+M Nr.	i
567 80	29



M22 M : F. Brass. Long.
Max. 400 bar

⊙	
1/4"	
3/8"	
1/2"	

R+M Nr.	i
565 251	40
565 401	40



M22 M : F. Brass. With hexagon.
Max. 400 bar

R+M Nr.	i
565 80	38



M22 M : F. Stainless steel.
Max. 500 bar

R+M Nr.	i
565 29	29
565 49	29
565 659	30

Quick screw nipples

Male thread : male thread



M22 M : M. Brass.
Max. 400 bar

⊙	
1/4"	
3/8"	
1/2"	

R+M Nr.	i
565 30	29 mm
565 50	29 mm
565 60	29 mm



M22 M : M with cone (AGR). Brass.
Max. 400 bar

R+M Nr.	i
565 301	31.5 mm
565 501	31.5 mm



M21 M : M. Brass.
Max. 400 bar

R+M Nr.	i
567 30	32 mm
567 50	32 mm



M22 M : M. Brass. Long.
Max. 400 bar

⊙	
1/4"	
3/8"	
1/2"	

R+M Nr.	i
565 311	40 mm
565 511	40 mm



M22 M : M. Stainless steel.
Max. 500 bar

R+M Nr.	i
565 39	29 mm
565 59	29 mm
565 69	29 mm



M22 M : M. Stainless steel.
Max. 400 bar

R+M Nr.	i
565 312 9	42 mm

* limited stock