

Handverschraubungen

Handverschraubungen mit Langnippel



HV M22 : IG.
Max. 400 bar / 150 °C



M22 AG : AG. Langbohrung.
Max. 400 bar / 150 °C

| |
|------|
| ☉ |
| 1/4" |
| 3/8" |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 561 31 | 40 mm |
| | |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 565 311 | 40 mm |
| 565 511 | 40 mm |



M22 AG : IG. Langbohrung.
Max. 400 bar / 150 °C



M22 AG : 1/4" AG. Langbohrung.
Max. 400 bar / 150 °C

| |
|------|
| ☉ |
| 1/4" |
| 3/8" |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 565 251 | 40 mm |
| 565 401 | 40 mm |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 565 311 9 | 40 mm |

Handverschraubungen mit Sechskantsperre



HV M22 : IG.
Max. 400 bar / 150 °C



M22 : IG. Innensechskant.
Max. 400 bar / 150 °C

| |
|------|
| ☉ |
| 1/4" |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 560 50 | 41 mm |

| | |
|----------------|-------|
| R+M Nr. | ⓘ |
| 565 80 | 38 mm |