

## easywash365+ swivels

Housing nickel-plated brass. Axle stainless steel. Field of application: Ceiling booms in self-service car wash



1/4" F : 1/4" M. DN 7.  
Max. 275 bar / 30 r.p.m. / 120 °C

R+M Nr.	Ø
562 390 503	46 mm



3/8" F : 1/4" M. DN 7.  
Max. 275 bar / 30 r.p.m. / 120 °C

R+M Nr.	Ø
562 390 505	46 mm



3/8" F : 3/8" M. DN 7.  
Max. 275 bar / 30 r.p.m. / 120 °C

R+M Nr.	Ø
562 390 507	46 mm



Repair kit **easywash365+** swivels

R+M Nr.
750 140 2

## easywash365+ swivels

Housing stainless steel / nickel-plated brass. Axle stainless steel. Maintenance-free. DN 6. Field of application: Swivels applicable to high pressure spray guns and hose connections, ceiling booms in self-service car wash



1/4" M : 1/4" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 600	63 mm	1
562 391 601	63 mm	25



1/4" M : 3/8" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 605	64 mm	1
562 391 606	64 mm	25



3/8" M : 1/4" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 610	63 mm	1
562 391 611	63 mm	25



3/8" M : 3/8" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 615	64 mm	1
562 391 616	64 mm	25



1/4" F : 1/4" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 620	69 mm	1
562 391 621	69 mm	25



3/8" F : 3/8" F.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 625	67 mm	1
562 391 626	67 mm	25



1/4" F : M18 M.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 630	62 mm	1
562 391 631	62 mm	25



1/4" F : M14 M.  
Max. 275 bar / 120 °C

R+M Nr.	Ø	VPE
562 391 627	62 mm	1
562 391 628	62 mm	25

## Mosmatic swivels WDG

Housing nickel-plated brass. Axle stainless steel. Field of application: Ceiling booms in self-service car wash



1/4" F : 1/4" M. DN 7.  
Max. 150 bar / 30 r.p.m. / 90 °C

R+M Nr.	Ø
750 140 11	46 mm



3/8" F : 1/4" M. DN 7.  
Max. 150 bar / 30 r.p.m. / 90 °C

R+M Nr.	Ø
750 140 1	46 mm



Repair kit  
Mosmatic swivels WDG

R+M Nr.
750 140 2