Mosmatic swivels DGS / DGV /DGK

Housing stainless steel / nickel-plated brass. Axle stainless steel. DN 6. Rust-proof and maintenance-free. Field of application: Swivels applicable to high pressure spray guns and hose connections, ceiling booms in self-service car wash. Max. 275 bar / 30 r.p.m. / 120 °C

DGS. Double ball bearing system

R+M Nr.	⇦	⇩	↔
108 300 01	1/4" F	1/4" M	59 mm
108 300 02	1/4" F	1/4" F	62 mm
108 300 04	1/4" F	3/8" F	63 mm
108 300 05	1/4" F	M14 M	57 mm
108 300 06	1/4" F	M16 M	57 mm
108 300 07	1/4" F	M18 M	57 mm
108 300 09	1/4" F	M22 M	61 mm
108 301 03	3/8" F	3/8" M	60 mm
108 301 04	3/8" F	3/8" F	63 mm
108 301 07	3/8" F	M18 M	57 mm
108 301 09	3/8" F	M22 M	61 mm

DGV. Single ball bearing system

R+M Nr.	⇦	⇩	↔
108 325 11	1/4" M	1/4" M	60 mm
108 325 12	1/4" M	1/4" F	63 mm
108 325 13	1/4" M	3/8" M	61 mm
108 325 21	3/8" M	1/4" M	60 mm
108 325 24	3/8" M	3/8" F	61 mm
108 325 32	3/8" M	1/4" F	63 mm
108 325 33	3/8" M	3/8" M	61 mm
108 325 34	3/8" M	3/8" F	63 mm
108 325 37	3/8" M	18 x 1.5" M	58 mm
108 325 39	3/8" M	22 x 1.5" M	62 mm
108 325 82	1/4" F	1/4" F	67 mm
108 325 87	1/4" F	18 x 1.5" M	62 mm

DGK. Single ball bearing system

R+M Nr.	⇦	⇩	↔
108 320 31	1/4" M	DN 06	58 mm
108 320 33	1/4" F	DN 06	62 mm

Mosmatic swivels DGE / DGEI

Axle stainless steel. Maintenance-free. Field of application: especially designed for high flow rates and low revolutions per minute as for example at automatic car wash plants. Max. 30 r.p.m. / 120 °C. DN 13 for 1/2". DN 25 for 1"

DGE 90°. Housing nickel-plated brass. Single ball bearing system. Rust-proof. Max. 275 bar

R+M Nr.	⇦	⇩	↔
108 348 23	1/2" F	1/2" M	91
108 348 25	1" F	1" M	113

DGE. Housing nickel-plated brass. Single ball bearing system. Rust-proof. Max. 275 bar

R+M Nr.	⇦	⇩	↔
108 348 03	1/2" F	1/2" M	80
108 348 05	1" F	1" M	90

DGEI. Housing stainless steel. Triple ball bearing system. Max. 350 bar

R+M Nr.	⇦	⇩	↔
108 347 03	1/2" F	1/2" M	80
108 347 05	1" F	1" M	95

DGEI 90°. Housing stainless steel. Triple ball bearing system. Max. 350 bar

R+M Nr.	⇦	⇩	↔
108 347 23	1/2" F	1/2" M	97
108 347 25	1" F	1" M	123

Symbols ↕ height ↔ length mm ⇩ outlet ⇦ inlet VPE packing unit