

R+M Drehgelenke



3/4" IG : 3/4" AG. DN 19.
Gehäuse und Achse Edelstahl.
Max. 200 bar / 90 °C

R+M Nr.	
750 400 1	80 mm



Dichtsatz Drehgelenk 750 400 1

R+M Nr.	
750 400 2	



3/8" AG : 3/8" IG.
Messing.
Max. 220 bar / 90 °C

R+M Nr.	
562 50	39 mm



1/4" IG : 3/8" AG. DN 6.
Gehäuse und Achse Edelstahl.
Max. 600 bar / 90 °C

R+M Nr.	
750 280 0	59 mm



Dichtsatz Drehgelenk 750 280 0

R+M Nr.	
750 200 2	



3/8" AG : 1/4" IG.
Messing.
Max. 220 bar / 90 °C

R+M Nr.	
562 60	39 mm

Hochdruckschnellkupplungen

Kupplungen 25KB



Kupplung : IG. Messing vernickelt. Mit Ventil.
Max. 35 bar / 100 °C

Stecknippel 25SB



Stecknippel : IG. \varnothing 12 mm. Messing. Mit Ventil.
Max. 35 bar / 100 °C

Stützring



TYP 25KF + 25KB

R+M Nr.
790 41

	DN
1/4"	7,4
3/8"	7,4

R+M Nr.	
553 20	55 mm
553 30	54 mm

R+M Nr.	
556 10	43 mm
556 30	43 mm

Symbole Höhe Länge mm **DN** Nennweite Gewinde Durchmesser Ausgang Eingang **TYP** Typ