

R+M swivels



3/4" F : 3/4" M. DN 19.
Housing and axle stainless steel.
Max. 200 bar / 90 °C

R+M Nr.	
750 400 1	80 mm



Repair kit swivel 750 400 1

R+M Nr.	
750 400 2	



3/8" M : 3/8" F.
Brass.
Max. 220 bar / 90 °C

R+M Nr.	
562 50	39 mm



1/4" F : 3/8" M. DN 6.
Housing and axle stainless steel.
Max. 600 bar / 90 °C

R+M Nr.	
750 280 0	59 mm



Seal kit swivel 750 280 0

R+M Nr.	
750 200 2	



3/8" M : 1/4" F.
Brass.
Max. 220 bar / 90 °C

R+M Nr.	
562 60	39 mm

High pressure quick couplings

Couplings 25KB



Coupling : F. Nickel-plated brass. With valve.
Max. 35 bar / 100 °C

Plugs 25SB



Plug : F. \varnothing 12 mm.
Brass. With valve.
Max. 35 bar / 100 °C

Back ring



25KF + 25KB

R+M Nr.
790 41

	DN
1/4"	7.4
3/8"	7.4

R+M Nr.	
553 20	55 mm
553 30	54 mm

R+M Nr.	
556 10	43 mm
556 30	43 mm

Symbols height length mm DN nominal diameter thread diameter outlet inlet type