

R+M swivels



3/4" F : 3/4" M.
DN 19.
Housing and axle stainless steel.
Max. 200 bar / 90 °C

R+M Nr.	ⓘ
750 400 1	80 mm



Repair kit swivel 750 400 1

R+M Nr.	ⓘ
750 400 2	



3/8" M : 3/8" F.
Brass.
Max. 220 bar / 90 °C

R+M Nr.	ⓘ
562 50	39 mm



M14 M : 1/4" F. Nickel-plated brass.
Axle stainless steel.
Double ball bearing system.
Max. 250 bar / 30 r.p.m. / 120 °C

R+M Nr.	ⓘ
562 391 506	61 mm



1/4" F : 3/8" M. DN 6.
Housing and axle stainless steel.
Max. 600 bar / 90 °C

R+M Nr.	ⓘ
750 280 0	59 mm



Seal kit swivel 750 280 0

R+M Nr.	ⓘ
750 200 2	



3/8" M : 1/4" F.
Brass.
Max. 220 bar / 90 °C

R+M Nr.	ⓘ
562 60	39 mm

High pressure quick couplings

Couplings 25KF



Coupling : F. Nickel-plated brass / nickel-plated steel.
Max. 250 bar / 100 °C



Coupling : M. Nickel-plated brass / nickel-plated steel.
Max. 250 bar / 100 °C

Plugs 25SF



Plug : F. \varnothing 12 mm. Nickel-plated steel.
Max. 250 bar / 100 °C



Plug : M. \varnothing 12 mm. Nickel-plated steel.
Max. 250 bar / 100 °C

⊙	DN
1/4"	7.4
3/8"	7.4

R+M Nr.	ⓘ
552 30	55 mm
552 50	54 mm

R+M Nr.	ⓘ
552 40	58 mm
552 60	57 mm

R+M Nr.	ⓘ
555 20	33 mm
555 40	33 mm

R+M Nr.	ⓘ
555 30	34 mm
555 50	33 mm

Couplings 25KB



Coupling : F. Nickel-plated brass. With valve.
Max. 35 bar / 100 °C



Plug : F. \varnothing 12 mm. Brass. With valve.
Max. 35 bar / 100 °C

Back ring



TYP 25KF + 25KB

R+M Nr.
790 41

⊙	DN
1/4"	7.4
3/8"	7.4

R+M Nr.	ⓘ
553 20	55 mm
553 30	54 mm

R+M Nr.	ⓘ
556 10	43 mm
556 30	43 mm

Symbols ⓘ height Ⓜ length mm DN nominal diameter ⊙ thread ⌀ diameter ⊖ outlet ⊕ inlet TYP type