

High pressure quick couplings

Couplings CEJN 322 and plug



Coupling : F. Chrome-plated brass /
chrome-plated steel.
Max. 200 bar / 100 °C



Coupling : F. Chrome-plated brass /
chrome-plated steel. With valve.
Max. 200 bar / 100 °C



Coupling : M. Chrome-plated brass /
chrome-plated steel.
Max. 200 bar / 100 °C

⊙	DN
1/4"	7.4
3/8"	7.4
M18	7.4

R+M Nr.	ⓘ
552 001	48 mm
552 002	50 mm
552 008	84 mm

R+M Nr.	ⓘ
552 031	57 mm
552 032	57 mm

R+M Nr.	ⓘ
552 011	45 mm
552 012	47 mm
552 018	69 mm



Plug : F. Ø 12 mm. Nickel-plated
steel. Max. 200 bar / 100 °C



Plug : M. Ø 12 mm. Nickel-plated
steel. Max. 200 bar / 100 °C

⊙	DN
1/4"	7.4
3/8"	7.4
M18	7.4

R+M Nr.	ⓘ
552 101	36 mm
552 102	38 mm

R+M Nr.	ⓘ
552 111	36 mm
552 112	38 mm
552 108	56 mm

Couplings SP-20 150 bar and plug



Coupling : F. Brass.
Max. 150 bar / 100 °C



Coupling : M. Brass.
Max. 150 bar / 100 °C



Plug : F. Ø 14.8 mm. Zinc-plated
steel. Max. 150 bar / 100 °C

⊙	DN
1/4"	8.0
3/8"	8.0
1/2"	8.0

R+M Nr.	ⓘ
550 10	41 mm
550 30	42 mm

R+M Nr.	ⓘ
550 20	43 mm

R+M Nr.	ⓘ
551 11	40 mm
551 10	40 mm



Plug : M. Ø 14.8 mm. Zinc-plated
steel. Max. 150 bar / 100 °C



O-ring. **TYP** SP-20. 13.1x2.6.
Max. 150 bar / 100 °C

⊙	DN
3/8"	8.0

R+M Nr.	ⓘ
551 20	43 mm

R+M Nr.	ⓘ
790 60	