

High pressure quick couplings

Couplings CEJN 322 and plug



Coupling : F.
Brass / steel, nickel-plated.
Max. 200 bar / 100 °C



Plug : F. Ø 12 mm.
Hardened steel, chemically nickel-plated / zinc-plated.
Max. 200 bar / 100 °C



Plug : M. Ø 12 mm.
Hardened steel, chemically nickel-plated / zinc-plated and brass.
Max. 200 bar / 100 °C

⊙	DN
1/4"	7.4
3/8"	7.4

R+M Nr.	ⓘ
552 001	48 mm
552 002	50 mm

R+M Nr.	ⓘ
552 101	36 mm
552 102	38 mm

R+M Nr.	ⓘ
552 111	36 mm
552 112	38 mm

Couplings SP-20 250 bar and plug



Coupling : F. Brass.
Max. 250 bar / 100 °C



Coupling : M. Brass.
Max. 250 bar / 100 °C



Plug : F. Ø 14.8 mm. Zinc-plated steel.
Max. 250 bar / 100 °C

⊙	DN
1/4"	8.0
3/8"	8.0
1/2"	8.0

R+M Nr.	ⓘ
550 10	41 mm
550 30	42 mm

R+M Nr.	ⓘ
550 20	43 mm

R+M Nr.	ⓘ
551 11	40 mm
551 10	40 mm



Plug : M. Ø 14.8 mm. Zinc-plated steel.
Max. 250 bar / 100 °C



O-ring. TYP SP-20. 13.1x2.6.
Max. 250 bar / 100 °C

⊙	DN
3/8"	8.0

R+M Nr.	ⓘ
551 20	43 mm

R+M Nr.	ⓘ
790 60	