


## Hose connectors



M22 M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 20



M21 M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 10



1/2" M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 30



M22 M. Standard. Stainless steel.  
Max. 400 bar

<b>R+M Nr.</b>
569 29



M22 M. Solid version stainless steel.  
Max. 500 bar

<b>R+M Nr.</b>
569 59



M22 M. DKOS stainless steel.  
Max. 500 bar

<b>R+M Nr.</b>
593 142



M24 M. Stainless steel.  
Max. 700 bar

<b>R+M Nr.</b>
200 741 600



M21 M : M22 M. Brass. Reduction.  
Max. 400 bar

<b>R+M Nr.</b>
569 15



M22 M. Solid version. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 50



Rubber cover

<b>R+M Nr.</b>
569 60



M22 M. Solid version with rubber cover.  
Max. 400 bar

<b>R+M Nr.</b>
569 40



M22 M. Long with moulded handle.  
Max. 280 bar

<b>R+M Nr.</b>
569 70



M21 M : M18 M. Brass. Reduction.  
Max. 400 bar

<b>R+M Nr.</b>
569 12




M24 F : M14x1 F. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 824

### Comparison chart of metric and bsp thread

female thread



male thread

pipe	IG	AG	metric	IG	AG
1/8" ( 5x10)	8.566 mm	9.728 mm	M12x1.5	10.38 mm	12 mm
1/4" ( 8x13)	11.445 mm	13.157 mm	M14x1.5	12.38 mm	14 mm
3/8" (12x17)	14.950 mm	16.662 mm	M16x1.5	14.38 mm	16 mm
1/2" (15x21)	18.631 mm	20.955 mm	M18x1.5	16.38 mm	18 mm
3/4" (21x27)	24.117 mm	26.441 mm	M21x1.5	19.38 mm	21 mm
1" (26x34)	30.291 mm	33.249 mm	M22x1.5	20.38 mm	22 mm
1.1/4" (33x42)	38.952 mm	41.910 mm	M24x1.5	22.38 mm	24 mm
1.1/2" (40x49)	44.324 mm	47.803 mm	M27x1.5	25.38 mm	27 mm
2" (50x60)	56.656 mm	59.614 mm	M30x1.5	28.38 mm	30 mm

Symbols IG female thread AG male thread ⌀ thread I height Ø diameter