

## Hose connectors



M22 M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 20



M21 M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 10



1/2" M. Standard. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 30



M22 M. Standard. Stainless steel.  
Max. 400 bar

<b>R+M Nr.</b>
569 29



M22 M. Solid version stainless steel.  
Max. 500 bar

<b>R+M Nr.</b>
569 59



M22 M. DKOS stainless steel.  
Max. 500 bar

<b>R+M Nr.</b>
593 142



M24 M. Stainless steel.  
Max. 700 bar

<b>R+M Nr.</b>
200 741 600



M21 M : M22 M. Brass. Reduction.  
Max. 400 bar

<b>R+M Nr.</b>
569 15



M22 M. Solid version. Brass.  
Max. 400 bar

<b>R+M Nr.</b>
569 50



Rubber cover

<b>R+M Nr.</b>
569 60



M22 M. Solid version with rubber cover.  
Max. 400 bar

<b>R+M Nr.</b>
569 40



M22 M. Long with moulded handle.  
Max. 280 bar

<b>R+M Nr.</b>
569 70



M21 M : M18 M. Brass. Reduction.  
Max. 400 bar

<b>R+M Nr.</b>
569 12



M22 M. Solid version stainless steel with rubber cover.  
Max. 500 bar


<b>R+M Nr.</b>
569 49

### Comparison chart of metric, bsp and trapezoidal thread

pipe	IG	AG	metric	IG	AG
1/8" ( 5x10)	8.566 mm	9.728 mm	M12x1.5	10.38 mm	12 mm
1/4" ( 8x13)	11.445 mm	13.157 mm	M14x1.5	12.38 mm	14 mm
3/8" (12x17)	14.950 mm	16.662 mm	M16x1.5	14.38 mm	16 mm
1/2" (15x21)	18.631 mm	20.955 mm	M18x1.5	16.38 mm	18 mm
3/4" (21x27)	24.117 mm	26.441 mm	M21x1.5	19.38 mm	21 mm
1" (26x34)	30.291 mm	33.249 mm	M22x1.5	20.38 mm	22 mm
1.1/4" (33x42)	38.952 mm	41.910 mm	M24x1.5	22.38 mm	24 mm
1.1/2" (40x49)	44.324 mm	47.803 mm	M27x1.5	25.38 mm	27 mm
2" (50x60)	56.656 mm	59.614 mm	M30x1.5	28.38 mm	30 mm

trapezoidal	IG	AG
TR20	18,1 mm	20 mm
TR22	20,1 mm	22 mm



## Hose adaptor



Plug 10 mm : M22 M.  
Max. 210 bar

<b>R+M Nr.</b>	<b>I</b>
316 951 0	190 mm



Plug 11 mm : M22 M.  
Max. 400 bar

<b>R+M Nr.</b>	<b>I</b>
316 961 1	190 mm



Plug 11 mm : M22 M.  
Max. 400 bar

<b>R+M Nr.</b>	<b>I</b>
316 961 2	145 mm
316 961 3	150 mm



M22 M : plug. Brass.  
Max. 250 bar / 100 °C

<b>R+M Nr.</b>	<b>I</b>
559 908 221	104 mm



Back ring

<b>R+M Nr.</b>	<b>O</b>
790 58	10 mm
790 59	11 mm



O-ring

<b>R+M Nr.</b>	<b>O</b>
790 55	10 mm
790 57	11 mm

Symbols **IG** female thread **AG** male thread **O** thread **I** height **Ø** diameter