

Hose adaptor



Plug coupling 10 mm : 3/8" M.
Max. 400 bar

R+M Nr.	
559 910 1	



Plug coupling 11 mm.
Max. 400 bar

R+M Nr.	
559 911 12	1/2" M
559 911 38	3/8" M
559 911 22	M22 M
559 911 23	M22 F



M22 F : M22 M. K 2000. Brass.
Max. 400 bar

R+M Nr.	
565 66	



Plug 10 mm : M22 M.
Max. 250 bar

R+M Nr.	
559 910 2	



O-ring

R+M Nr.	
790 55	10 mm



M18 M : TR20 F. K-Lock 8. Brass.
Max. 400 bar / 150° C

R+M Nr.	
565 686	



1/4" F : TR20 M. K-Lock 5. Brass.
For rotating nozzles.
Max. 400 bar / 150° C

R+M Nr.	
565 685	



O-ring. 10x2.2. Perbunan

R+M Nr.	
790 25	1
790 251 00	100



O-ring. 9.5x2

R+M Nr.	
050 002 456	1



Copper washer. K 2000

R+M Nr.	
781 519 1	18.8 mm



Back ring

R+M Nr.	
790 58	10 mm



M24 M : M. Brass *.
Max. 400 bar

R+M Nr.	
318 241 8	M18
318 242 1	M21



M27 M : M. Brass *.
Max. 400 bar

R+M Nr.	
318 271 8	M18
318 272 1	M21



3/8" M : TR22 F. K-Lock 5. Brass.
Max. 400 bar / 150° C

R+M Nr.	
565 683	



3/8" F : TR22 F. K-Lock 5. Brass.
Max. 400 bar / 150° C

R+M Nr.	
565 684	



M24 M : 3/8" F. Brass *.
Max. 400 bar

R+M Nr.	
318 24	



M27 M : 3/8" F. Brass *.
Max. 400 bar

R+M Nr.	
318 27	



M22 M : TR22 F. K-Lock 5. Brass.
Max. 400 bar / 150° C

R+M Nr.	
565 681	



O-ring

R+M Nr.	
791 42	M24



O-ring

R+M Nr.	
903 598 00	M27

* not to be used with patented WAP / Venturi inserts