

## Hose adapter



Plug coupling 10 mm : 3/8" M.  
Max. 400 bar

R+M Nr.	
559 910 1	



Plug coupling 11 mm.  
Max. 400 bar

R+M Nr.	
559 911 12	1/2" M
559 911 38	3/8" M
559 911 22	M22 M
559 911 23	M22 F



M22 F : M22 M. K 2000. Brass.  
Max. 400 bar

R+M Nr.	
565 66	



Plug 10 mm : M22 M.  
Max. 250 bar

R+M Nr.	
559 910 2	



O-ring

R+M Nr.	
790 55	10 mm



M24 M : M. Brass \*.  
Max. 400 bar

R+M Nr.	
318 241 8	M18
318 242 1	M21



M27 M : M. Brass \*.  
Max. 400 bar

R+M Nr.	
318 271 8	M18
318 272 1	M21



M24 M : 3/8" F. Brass \*.  
Max. 400 bar

R+M Nr.	
318 24	



M27 M : 3/8" F. Brass \*.  
Max. 400 bar

R+M Nr.	
318 27	



Copper washer. K 2000

R+M Nr.	
781 519 1	18.8 mm



Back ring

R+M Nr.	
790 58	10 mm



O-ring

R+M Nr.	
791 42	M24



O-ring

R+M Nr.	
903 598 00	M27



O-ring. 10x2.2. Perbunan

R+M Nr.	
790 25	1
790 251 00	100



O-ring. 9.5x2

R+M Nr.	
050 002 456	1

## Reduction nipple

Female thread : male thread



Brass. Max. 400 bar

R+M Nr.	
710 100 032	
710 100 033	

IG : AG	
1/4" : M12x1	
M12x1 : 1/4"	

\* not to be used with patented WAP / Venturi inserts