

High pressure hoses with *wrapped cover*Hoses with single wire braid and *wrapped cover*

| TYP | DN | P       | °C     | ↔    | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     |
|-----|----|---------|--------|------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 1SN | 6  | 210 bar | 150 °C | 10 m |             | 330 110 310 | 330 128 310 | 330 104 310 | 330 103 310 |             | 330 112 310 | 330 113 310 |
|     |    |         |        | 15 m |             | 330 110 315 | 330 128 315 | 330 104 315 | 330 103 315 |             | 330 112 315 | 330 113 315 |
|     |    |         |        | 20 m |             | 330 110 320 | 330 128 320 | 330 104 320 | 330 103 320 |             | 330 112 320 | 330 113 320 |
| 1SN | 8  | 210 bar | 150 °C | 10 m | 340 110 410 |             |             | 340 104 310 | 340 103 310 | 340 194 310 | 340 112 310 | 340 113 310 |
|     |    |         |        | 15 m | 340 110 415 |             |             | 340 104 315 | 340 103 315 | 340 194 315 | 340 112 315 | 340 113 315 |
|     |    |         |        | 20 m | 340 110 420 |             |             | 340 104 320 | 340 103 320 | 340 194 320 | 340 112 320 | 340 113 320 |
| 1SN | 8  | 315 bar | 150 °C | 10 m | 343 110 410 |             |             | 343 104 310 | 343 103 310 |             | 343 112 310 | 343 113 310 |
|     |    |         |        | 15 m | 343 110 415 |             |             | 343 104 315 | 343 103 315 |             | 343 112 315 | 343 113 315 |
|     |    |         |        | 20 m | 343 110 420 |             |             | 343 104 320 | 343 103 320 |             | 343 112 320 | 343 113 320 |
| 1SN | 10 | 210 bar | 150 °C | 10 m |             |             |             | 350 104 310 | 350 103 310 |             |             | 350 113 310 |
|     |    |         |        | 15 m |             |             |             | 350 104 315 | 350 103 315 |             |             | 350 113 315 |
|     |    |         |        | 20 m |             |             |             | 350 104 320 | 350 103 320 |             |             | 350 113 320 |

Hoses with double wire braid and *wrapped cover*

| TYP | DN | P       | °C     | ↔    | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr.     | R+M Nr. | R+M Nr.     | R+M Nr.     |
|-----|----|---------|--------|------|-------------|-------------|-------------|-------------|-------------|---------|-------------|-------------|
| 2SC | 6  | 400 bar | 150 °C | 10 m |             | 335 110 310 | 335 128 310 | 335 104 310 | 335 103 310 |         | 335 112 310 | 335 113 310 |
|     |    |         |        | 15 m |             | 335 110 315 | 335 128 315 | 335 104 315 | 335 103 315 |         | 335 112 315 | 335 113 315 |
|     |    |         |        | 20 m |             | 335 110 320 | 335 128 320 | 335 104 320 | 335 103 320 |         | 335 112 320 | 335 113 320 |
| 2SC | 8  | 400 bar | 150 °C | 10 m | 345 110 410 |             |             | 345 104 310 | 345 103 310 |         | 345 112 310 | 345 113 310 |
|     |    |         |        | 15 m | 345 110 415 |             |             | 345 104 315 | 345 103 315 |         | 345 112 315 | 345 113 315 |
|     |    |         |        | 20 m | 345 110 420 |             |             | 345 104 320 | 345 103 320 |         | 345 112 320 | 345 113 320 |
| 2SC | 10 | 400 bar | 150 °C | 10 m |             |             |             | 355 104 310 | 355 103 310 |         |             | 355 113 310 |
|     |    |         |        | 15 m |             |             |             | 355 104 315 | 355 103 315 |         |             | 355 113 315 |
|     |    |         |        | 20 m |             |             |             | 355 104 320 | 355 103 320 |         |             | 355 113 320 |

Hoses with single wire braid and *wrapped thick cover*

| TYP | DN | P       | °C     | ↔    | R+M Nr.     | R+M Nr. | R+M Nr. | R+M Nr.     | R+M Nr.     | R+M Nr. | R+M Nr.     | R+M Nr.     |
|-----|----|---------|--------|------|-------------|---------|---------|-------------|-------------|---------|-------------|-------------|
| 1ST | 8  | 210 bar | 150 °C | 10 m | 340 210 410 |         |         | 340 204 310 | 340 203 310 |         | 340 212 310 | 340 213 310 |
|     |    |         |        | 15 m | 340 210 415 |         |         | 340 204 315 | 340 203 315 |         | 340 212 315 | 340 213 315 |
|     |    |         |        | 20 m | 340 210 420 |         |         | 340 204 320 | 340 203 320 |         | 340 212 320 | 340 213 320 |
| 1ST | 10 | 210 bar | 150 °C | 10 m |             |         |         | 350 204 310 | 350 203 310 |         |             | 350 213 310 |
|     |    |         |        | 15 m |             |         |         | 350 204 315 | 350 203 315 |         |             | 350 213 315 |
|     |    |         |        | 20 m |             |         |         | 350 204 320 | 350 203 320 |         |             | 350 213 320 |

\* not to be used for patented Kärcher guns.

All fittings are made out of zinc-plated steel. The hoses are also available with stainless steel fittings.

Please be so kind as to state the following on your order: R+M Nr. plus number:

7 = plug and crimp stainless steel 8 = plug stainless steel 9 = plug, crimp and connection stainless steel

Our hose assemblies are durably marked on the crimp in accordance with EN 853 / EN 856 / EN 855.

Symbols  $\varnothing$  diameter DN nominal diameter P pressure °C temperature ↔ length TYP type