

High pressure hoses with *smooth* cover



Hoses with single wire braid and *smooth* cover

| TYP | DN | P | °C | ↔ | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. |
|-------|----|---------|--------|------|-------------|-------------|---------|-------------|-------------|---------|-------------|-------------|
| Flexy | 6 | 300 bar | 100 °C | 10 m | 390 074 210 | 390 076 210 | | 390 052 210 | 390 054 210 | | 390 042 210 | 390 044 210 |
| | | | | | 390 074 215 | 390 076 215 | | 390 052 215 | 390 054 215 | | 390 042 215 | 390 044 215 |
| | | | | | 390 074 220 | 390 076 220 | | 390 052 220 | 390 054 220 | | 390 042 220 | 390 044 220 |

Hoses with single wire braid and *smooth* cover

| TYP | DN | P | °C | ↔ | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | |
|-----|----|---------|--------|------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 1SN | 8 | 250 bar | 150 °C | 10 m | 340 674 310 | 340 676 310 | | 340 652 310 | 340 654 310 | | 340 642 310 | 340 644 310 | |
| | | | | | 340 674 315 | 340 676 315 | | 340 652 315 | 340 654 315 | | 340 642 315 | 340 644 315 | |
| | | | | | 340 674 320 | 340 676 320 | | 340 652 320 | 340 654 320 | | 340 642 320 | 340 644 320 | |
| 1SN | 10 | 210 bar | 150 °C | 10 m | | 350 676 310 | 350 668 310 | | 350 654 310 | 350 656 310 | 350 642 310 | 350 644 310 | 350 646 310 |
| | | | | | | 350 676 315 | 350 668 315 | | 350 654 315 | 350 656 315 | 350 642 315 | 350 644 315 | 350 646 315 |
| | | | | | | 350 676 320 | 350 668 320 | | 350 654 320 | 350 656 320 | 350 642 320 | 350 644 320 | 350 646 320 |

Hoses with double wire braid and *smooth* cover

| TYP | DN | P | °C | ↔ | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | R+M Nr. | |
|-----|----|---------|--------|------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 2SN | 8 | 400 bar | 150 °C | 10 m | 345 674 310 | 345 676 310 | | 345 652 310 | 345 654 310 | | 345 642 310 | 345 644 310 | |
| | | | | | 345 674 315 | 345 676 315 | | 345 652 315 | 345 654 315 | | 345 642 315 | 345 644 315 | |
| | | | | | 345 674 320 | 345 676 320 | | 345 652 320 | 345 654 320 | | 345 642 320 | 345 644 320 | |
| 2SN | 10 | 400 bar | 150 °C | 10 m | | 355 676 310 | 355 668 310 | | 355 654 310 | 355 656 310 | 355 642 310 | 355 644 310 | 355 646 310 |
| | | | | | | 355 676 315 | 355 668 315 | | 355 654 315 | 355 656 315 | 355 642 315 | 355 644 315 | 355 646 315 |
| | | | | | | 355 676 320 | 355 668 320 | | 355 654 320 | 355 656 320 | 355 642 320 | 355 644 320 | 355 646 320 |

All fittings are made out of zinc-plated steel. The hoses are also available with stainless steel fittings.

Please be so kind as to state the following on your order: R+M Nr. plus number:

7 = plug and crimp stainless steel 8 = plug stainless steel 9 = plug, crimp and connection stainless steel