

High pressure hoses with *smooth* cover



Hoses with single wire braid and *smooth* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
Flexy	6	300 bar	100 °C	10 m	390 074 210	390 076 210		390 052 210	390 054 210		390 042 210	390 044 210
					390 074 215	390 076 215		390 052 215	390 054 215		390 042 215	390 044 215
					390 074 220	390 076 220		390 052 220	390 054 220		390 042 220	390 044 220

Hoses with single wire braid and *smooth* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
1SN	8	250 bar	150 °C	10 m	340 674 310	340 676 310		340 652 310	340 654 310		340 642 310	340 644 310
					340 674 315	340 676 315		340 652 315	340 654 315		340 642 315	340 644 315
					340 674 320	340 676 320		340 652 320	340 654 320		340 642 320	340 644 320
1SN	10	210 bar	150 °C	10 m		350 676 310	350 668 310		350 654 310	350 656 310	350 642 310	350 644 310
						350 676 315	350 668 315		350 654 315	350 656 315	350 642 315	350 644 315
						350 676 320	350 668 320		350 654 320	350 656 320	350 642 320	350 644 320

Hoses with double wire braid and *smooth* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
2SN	8	400 bar	150 °C	10 m	345 674 310	345 676 310		345 652 310	345 654 310		345 642 310	345 644 310
					345 674 315	345 676 315		345 652 315	345 654 315		345 642 315	345 644 315
					345 674 320	345 676 320		345 652 320	345 654 320		345 642 320	345 644 320
2SN	10	400 bar	150 °C	10 m		355 676 310	355 668 310		355 654 310	355 656 310	355 642 310	355 644 310
						355 676 315	355 668 315		355 654 315	355 656 315	355 642 315	355 644 315
						355 676 320	355 668 320		355 654 320	355 656 320	355 642 320	355 644 320

All fittings are made out of zinc-plated steel. The hoses are also available with stainless steel fittings.

Please be so kind as to state the following on your order: R+M Nr. plus number:

7 = plug and crimp stainless steel 8 = plug stainless steel 9 = plug, crimp and connection stainless steel