

High pressure hoses with *smooth* coverHoses with single wire braid and *smooth* cover

| TYP   | DN | P       | °C     | ↔    | R+M Nr.       | R+M Nr.       | R+M Nr.       | R+M Nr.       |
|-------|----|---------|--------|------|---------------|---------------|---------------|---------------|
| Flexy | 6  | 300 bar | 100 °C | 10 m | 390 000 321 0 | 390 001 121 0 | 390 011 321 0 | 390 010 321 0 |
|       |    |         |        | 15 m | 390 000 321 5 | 390 001 121 5 | 390 011 321 5 | 390 010 321 5 |
|       |    |         |        | 20 m | 390 000 322 0 | 390 001 122 0 | 390 011 322 0 | 390 010 322 0 |
| 1SN   | 8  | 250 bar | 150 °C | 10 m | 340 600 321 0 | 340 601 121 0 | 340 611 321 0 | 340 610 321 0 |
|       |    |         |        | 15 m | 340 600 321 5 | 340 601 121 5 | 340 611 321 5 | 340 610 321 5 |
|       |    |         |        | 20 m | 340 600 322 0 | 340 601 122 0 | 340 611 322 0 | 340 610 322 0 |
| 1SN   | 8  | 315 bar | 150 °C | 10 m | 343 600 321 0 | 343 601 121 0 | 343 611 321 0 | 343 610 321 0 |
|       |    |         |        | 15 m | 343 600 321 5 | 343 601 121 5 | 343 611 321 5 | 343 610 321 5 |
|       |    |         |        | 20 m | 343 600 322 0 | 343 601 122 0 | 343 611 322 0 | 343 610 322 0 |
| 1SN   | 10 | 210 bar | 150 °C | 10 m | 350 600 321 0 | 350 601 121 0 |               |               |
|       |    |         |        | 15 m | 350 600 321 5 | 350 601 121 5 |               |               |
|       |    |         |        | 20 m | 350 600 322 0 | 350 601 122 0 |               |               |

Hoses with double wire braid and *smooth* cover

| TYP | DN | P       | °C     | ↔    | R+M Nr.       | R+M Nr.       | R+M Nr.       | R+M Nr. |
|-----|----|---------|--------|------|---------------|---------------|---------------|---------|
| 2SN | 8  | 400 bar | 150 °C | 10 m | 345 600 321 0 | 345 601 121 0 | 345 611 321 0 |         |
|     |    |         |        | 15 m | 345 600 321 5 | 345 601 121 5 | 345 611 321 5 |         |
|     |    |         |        | 20 m | 345 600 322 0 | 345 601 122 0 | 345 611 322 0 |         |
| 2SN | 10 | 400 bar | 150 °C | 10 m | 355 600 321 0 |               |               |         |
|     |    |         |        | 15 m | 355 600 321 5 |               |               |         |
|     |    |         |        | 20 m | 355 600 322 0 |               |               |         |

Our hose assemblies are durably marked on the crimp in accordance with EN 853 / EN 856 / EN 855.

**Symbols**  $\varnothing$  diameter DN nominal diameter P pressure °C temperature ↔ length TYP type