

## CARWASH COMFORT - the new hose wonder in self-service washing bays

1/4" : 1/4"



Female thread (DKR)

R+M Nr.	↔	length
463 052 303 5	↔	3.5 m
463 052 303 7	↔	3.7 m
463 052 304	↔	4.0 m
463 052 304 2	↔	4.2 m
463 052 304 5	↔	4.5 m
463 052 304 7	↔	4.7 m
463 052 305	↔	5.0 m
463 052 305 5	↔	5.5 m
463 052 306	↔	6.0 m


3/8" : 3/8"



Female thread (DKR)

R+M Nr.	↔	length
463 054 303 5	↔	3.5 m
463 054 303 7	↔	3.7 m
463 054 304	↔	4.0 m
463 054 304 2	↔	4.2 m
463 054 304 5	↔	4.5 m
463 054 304 7	↔	4.7 m
463 054 305	↔	5.0 m
463 054 305 5	↔	5.5 m
463 054 306	↔	6.0 m

M14 : M14



Female thread (DKOL)

R+M Nr.	↔	length
463 072 303 5	↔	3.5 m
463 072 303 7	↔	3.7 m
463 072 304	↔	4.0 m
463 072 304 2	↔	4.2 m
463 072 304 5	↔	4.5 m
463 072 304 7	↔	4.7 m
463 072 305	↔	5.0 m
463 072 305 5	↔	5.5 m
463 072 306	↔	6.0 m

M18 : M18



Female thread (DKOL)

R+M Nr.	↔	length
463 076 303 5	↔	3.5 m
463 076 303 7	↔	3.7 m
463 076 304	↔	4.0 m
463 076 304 2	↔	4.2 m
463 076 304 5	↔	4.5 m
463 076 304 7	↔	4.7 m
463 076 305	↔	5.0 m
463 076 305 5	↔	5.5 m
463 076 306	↔	6.0 m

3/8" : 3/8"



Male thread (AGR)

R+M Nr.	↔	length
463 044 303 5	↔	3.5 m
463 044 303 7	↔	3.7 m
463 044 304	↔	4.0 m
463 044 304 2	↔	4.2 m
463 044 304 5	↔	4.5 m
463 044 304 7	↔	4.7 m
463 044 305	↔	5.0 m
463 044 305 5	↔	5.5 m
463 044 306	↔	6.0 m



Female thread (DKR)

R+M Nr.	↔	length
464 052 303 5	↔	3.5 m
464 052 303 7	↔	3.7 m
464 052 304	↔	4.0 m
464 052 304 2	↔	4.2 m
464 052 304 5	↔	4.5 m
464 052 304 7	↔	4.7 m
464 052 305	↔	5.0 m
464 052 305 5	↔	5.5 m
464 052 306	↔	6.0 m



Female thread (DKR)

R+M Nr.	↔	length
464 054 303 5	↔	3.5 m
464 054 303 7	↔	3.7 m
464 054 304	↔	4.0 m
464 054 304 2	↔	4.2 m
464 054 304 5	↔	4.5 m
464 054 304 7	↔	4.7 m
464 054 305	↔	5.0 m
464 054 305 5	↔	5.5 m
464 054 306	↔	6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
464 072 303 5	↔	3.5 m
464 072 303 7	↔	3.7 m
464 072 304	↔	4.0 m
464 072 304 2	↔	4.2 m
464 072 304 5	↔	4.5 m
464 072 304 7	↔	4.7 m
464 072 305	↔	5.0 m
464 072 305 5	↔	5.5 m
464 072 306	↔	6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
464 076 303 5	↔	3.5 m
464 076 303 7	↔	3.7 m
464 076 304	↔	4.0 m
464 076 304 2	↔	4.2 m
464 076 304 5	↔	4.5 m
464 076 304 7	↔	4.7 m
464 076 305	↔	5.0 m
464 076 305 5	↔	5.5 m
464 076 306	↔	6.0 m



Male thread (AGR)

R+M Nr.	↔	length
464 044 303 5	↔	3.5 m
464 044 303 7	↔	3.7 m
464 044 304	↔	4.0 m
464 044 304 2	↔	4.2 m
464 044 304 5	↔	4.5 m
464 044 304 7	↔	4.7 m
464 044 305	↔	5.0 m
464 044 305 5	↔	5.5 m
464 044 306	↔	6.0 m



Female thread (DKR)

R+M Nr.	↔	length
465 052 303 5	↔	3.5 m
465 052 303 7	↔	3.7 m
465 052 304	↔	4.0 m
465 052 304 2	↔	4.2 m
465 052 304 5	↔	4.5 m
465 052 304 7	↔	4.7 m
465 052 305	↔	5.0 m
465 052 305 5	↔	5.5 m
465 052 306	↔	6.0 m



Female thread (DKR)

R+M Nr.	↔	length
465 054 303 5	↔	3.5 m
465 054 303 7	↔	3.7 m
465 054 304	↔	4.0 m
465 054 304 2	↔	4.2 m
465 054 304 5	↔	4.5 m
465 054 304 7	↔	4.7 m
465 054 305	↔	5.0 m
465 054 305 5	↔	5.5 m
465 054 306	↔	6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
465 072 303 5	↔	3.5 m
465 072 303 7	↔	3.7 m
465 072 304	↔	4.0 m
465 072 304 2	↔	4.2 m
465 072 304 5	↔	4.5 m
465 072 304 7	↔	4.7 m
465 072 305	↔	5.0 m
465 072 305 5	↔	5.5 m
465 072 306	↔	6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
465 076 303 5	↔	3.5 m
465 076 303 7	↔	3.7 m
465 076 304	↔	4.0 m
465 076 304 2	↔	4.2 m
465 076 304 5	↔	4.5 m
465 076 304 7	↔	4.7 m
465 076 305	↔	5.0 m
465 076 305 5	↔	5.5 m
465 076 306	↔	6.0 m



Male thread (AGR)

R+M Nr.	↔	length
465 044 303 5	↔	3.5 m
465 044 303 7	↔	3.7 m
465 044 304	↔	4.0 m
465 044 304 2	↔	4.2 m
465 044 304 5	↔	4.5 m
465 044 304 7	↔	4.7 m
465 044 305	↔	5.0 m
465 044 305 5	↔	5.5 m
465 044 306	↔	6.0 m

Symbols ↔ length ∅ diameter