

## CARWASH COMFORT - the new hose wonder in self-service washing bays

1/4" : 1/4"		3/8" : 3/8"		M14 : M14		M18 : M18		3/8" : 3/8"	
Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
463 052 303 5	3.5 m	463 054 303 5	3.5 m	463 072 303 5	3.5 m	463 076 303 5	3.5 m	463 044 303 5	3.5 m
463 052 303 7	3.7 m	463 054 303 7	3.7 m	463 072 303 7	3.7 m	463 076 303 7	3.7 m	463 044 303 7	3.7 m
463 052 304	4.0 m	463 054 304	4.0 m	463 072 304	4.0 m	463 076 304	4.0 m	463 044 304	4.0 m
463 052 304 2	4.2 m	463 054 304 2	4.2 m	463 072 304 2	4.2 m	463 076 304 2	4.2 m	463 044 304 2	4.2 m
463 052 304 5	4.5 m	463 054 304 5	4.5 m	463 072 304 5	4.5 m	463 076 304 5	4.5 m	463 044 304 5	4.5 m
463 052 304 7	4.7 m	463 054 304 7	4.7 m	463 072 304 7	4.7 m	463 076 304 7	4.7 m	463 044 304 7	4.7 m
463 052 305	5.0 m	463 054 305	5.0 m	463 072 305	5.0 m	463 076 305	5.0 m	463 044 305	5.0 m
463 052 305 5	5.5 m	463 054 305 5	5.5 m	463 072 305 5	5.5 m	463 076 305 5	5.5 m	463 044 305 5	5.5 m
463 052 306	6.0 m	463 054 306	6.0 m	463 072 306	6.0 m	463 076 306	6.0 m	463 044 306	6.0 m
Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
464 052 303 5	3.5 m	464 054 303 5	3.5 m	464 072 303 5	3.5 m	464 076 303 5	3.5 m	464 044 303 5	3.5 m
464 052 303 7	3.7 m	464 054 303 7	3.7 m	464 072 303 7	3.7 m	464 076 303 7	3.7 m	464 044 303 7	3.7 m
464 052 304	4.0 m	464 054 304	4.0 m	464 072 304	4.0 m	464 076 304	4.0 m	464 044 304	4.0 m
464 052 304 2	4.2 m	464 054 304 2	4.2 m	464 072 304 2	4.2 m	464 076 304 2	4.2 m	464 044 304 2	4.2 m
464 052 304 5	4.5 m	464 054 304 5	4.5 m	464 072 304 5	4.5 m	464 076 304 5	4.5 m	464 044 304 5	4.5 m
464 052 304 7	4.7 m	464 054 304 7	4.7 m	464 072 304 7	4.7 m	464 076 304 7	4.7 m	464 044 304 7	4.7 m
464 052 305	5.0 m	464 054 305	5.0 m	464 072 305	5.0 m	464 076 305	5.0 m	464 044 305	5.0 m
464 052 305 5	5.5 m	464 054 305 5	5.5 m	464 072 305 5	5.5 m	464 076 305 5	5.5 m	464 044 305 5	5.5 m
464 052 306	6.0 m	464 054 306	6.0 m	464 072 306	6.0 m	464 076 306	6.0 m	464 044 306	6.0 m
Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
465 052 303 5	3.5 m	465 054 303 5	3.5 m	465 072 303 5	3.5 m	465 076 303 5	3.5 m	465 044 303 5	3.5 m
465 052 303 7	3.7 m	465 054 303 7	3.7 m	465 072 303 7	3.7 m	465 076 303 7	3.7 m	465 044 303 7	3.7 m
465 052 304	4.0 m	465 054 304	4.0 m	465 072 304	4.0 m	465 076 304	4.0 m	465 044 304	4.0 m
465 052 304 2	4.2 m	465 054 304 2	4.2 m	465 072 304 2	4.2 m	465 076 304 2	4.2 m	465 044 304 2	4.2 m
465 052 304 5	4.5 m	465 054 304 5	4.5 m	465 072 304 5	4.5 m	465 076 304 5	4.5 m	465 044 304 5	4.5 m
465 052 304 7	4.7 m	465 054 304 7	4.7 m	465 072 304 7	4.7 m	465 076 304 7	4.7 m	465 044 304 7	4.7 m
465 052 305	5.0 m	465 054 305	5.0 m	465 072 305	5.0 m	465 076 305	5.0 m	465 044 305	5.0 m
465 052 305 5	5.5 m	465 054 305 5	5.5 m	465 072 305 5	5.5 m	465 076 305 5	5.5 m	465 044 305 5	5.5 m
465 052 306	6.0 m	465 054 306	6.0 m	465 072 306	6.0 m	465 076 306	6.0 m	465 044 306	6.0 m

Symbols ↔ length ∅ diameter