

CARWASH COMFORT - erleben Sie unser blaues Wunder in Nennweite 8!

Hochzugfeste Polyesterarmierung, Arbeitsdruckbeständigkeit bis 200 bar. DN 8. -40 °C – +60 °C, -40 °F – +140 °F

1/4" : 1/4"



Dichtkegel (DKR)

R+M Nr.	↔	
471 052 603 5	3,5 m	
471 052 603 7	3,7 m	
471 052 604	4,0 m	
471 052 604 2	4,2 m	
471 052 604 5	4,5 m	
471 052 604 7	4,7 m	
471 052 605	5,0 m	
471 052 605 5	5,5 m	
471 052 606	6,0 m	

3/8" : 3/8"



Dichtkegel (DKR)

R+M Nr.	↔	
471 054 603 5	3,5 m	
471 054 603 7	3,7 m	
471 054 604	4,0 m	
471 054 604 2	4,2 m	
471 054 604 5	4,5 m	
471 054 604 7	4,7 m	
471 054 605	5,0 m	
471 054 605 5	5,5 m	
471 054 606	6,0 m	

M14 : M14



Dichtkegel (DKOL)

R+M Nr.	↔	
471 072 603 5	3,5 m	
471 072 603 7	3,7 m	
471 072 604	4,0 m	
471 072 604 2	4,2 m	
471 072 604 5	4,5 m	
471 072 604 7	4,7 m	
471 072 605	5,0 m	
471 072 605 5	5,5 m	
471 072 606	6,0 m	

M18 : M18



Dichtkegel (DKOL)

R+M Nr.	↔	
471 076 603 5	3,5 m	
471 076 603 7	3,7 m	
471 076 604	4,0 m	
471 076 604 2	4,2 m	
471 076 604 5	4,5 m	
471 076 604 7	4,7 m	
471 076 605	5,0 m	
471 076 605 5	5,5 m	
471 076 606	6,0 m	

3/8" : 3/8"



AGR : AGR

R+M Nr.	↔	
471 044 603 5	3,5 m	
471 044 603 7	3,7 m	
471 044 604	4,0 m	
471 044 604 2	4,2 m	
471 044 604 5	4,5 m	
471 044 604 7	4,7 m	
471 044 605	5,0 m	
471 044 605 5	5,5 m	
471 044 606	6,0 m	

Hochdruckschläuche für SB-Waschanlagen

Hochdruckschläuche mit einer Drahteinlage und gewickelter Decke. 15N. Nennweite 6. Max. 210 bar /150 °C

1/4" : 1/4"



Dichtkegel (DKR)

R+M Nr.	↔	
331 152 803 5	3,5 m	
331 152 804 2	4,2 m	
331 152 805	5,0 m	

3/8" : 3/8"



Dichtkegel (DKR)

R+M Nr.	↔	
331 154 803 5	3,5 m	
331 154 804 2	4,2 m	
331 154 805	5,0 m	

1/4" : 1/4"



Dichtkegel (DKR)

R+M Nr.	↔	
331 152 603 5	3,5 m	
331 152 604	4,0 m	
331 152 604 2	4,2 m	
331 152 605 5	5,5 m	

M14 : M14



Dichtkegel (DKOL) VA

R+M Nr.	↔	
331 172 803 59	3,5 m	
331 172 804 29	4,2 m	
331 172 804 79	4,7 m	

M14 : M14



Dichtkegel (DKOL)


R+M Nr.	↔	
331 172 803 5	3,5 m	
331 172 804	4,0 m	
331 172 805	5,0 m	

M22 : 10 dreh.



HV : Stecknippel mit Lager

R+M Nr.	↔	
330 117 303 5	3,5 m	
330 117 304	4,0 m	
330 117 304 2	4,2 m	
330 117 310	10,0 m	



HV : Stecknippel mit Lager

R+M Nr.	↔	
331 117 303 5	3,5 m	
331 117 304	4,0 m	
331 117 304 2	4,2 m	
331 117 305	5,0 m	
331 117 310	10,0 m	

Weitere Hochdruckschläuche für SB-Waschanlagen liefern wir auf Anfrage.