

Foodjet - food hose

Foodjet - Food hose according to EN 854. Particularly resistant to animal and poultry fats

- » Field of application: cleaning hose designed for the food industry
- » Suitable for: oil, water, water-in-oil emulsion and water mixes with up to 50 % detergent
- » Surface synthetic rubber. Particularly abrasion-, oil-, ozone-resistant, weatherproof and food safe
- » Interior synthetic, oil-resistant rubber
- » 2 tight textile meshwork
- » Max. 80 bar. Burst pressure > 240 bar.
-40 °C - +150 °C.

Foodjet per metre

DN 12

R+M Nr.	↔
303 60	10 - 95 m

Female thread DKR

1/2" : 1/2"



Fittings stainless steel

R+M Nr.	↔
490 056 002 59	2.5 m
490 056 010 9	10.0 m
490 056 015 9	15.0 m
490 056 020 9	20.0 m
490 056 025 9	25.0 m
490 056 030 9	30.0 m
490 056 035 9	35.0 m
490 056 040 9	40.0 m

Male thread (AGR)

1/2" : 1/2"



Fittings stainless steel

R+M Nr.	↔
490 046 002 59	2.5 m
490 046 010 9	10.0 m
490 046 015 9	15.0 m
490 046 020 9	20.0 m
490 046 025 9	25.0 m
490 046 030 9	30.0 m
490 046 035 9	35.0 m
490 046 040 9	40.0 m

Ball valves

Coupling ST-3100 : 1/2" F. Ball valve with safety guard

R+M Nr.
203 100 200



Coupling ST-3100 : plug ST-3100. Ball valve with safety guard

R+M Nr.
203 100 210

Symbols ↔ length DN nominal diameter P pressure S wall thickness BP burst pressure