

## Galvanator - food hose

Interior synthetic rubber. Resistant to usual detergents. Very temperature-resistant. Double zinc-plated steel wire braid. Surface special synthetic rubber. **Resistant to poultry fats.** Non Marking (soot free). Field of application: poultry farms, slaughterhouses, fishing, bakeries etc. Not suitable for swimming baths, standard and industrial cleaning applications.

The advantages of the zinc-plated steel braids become obvious when effecting a salt water test. The Galvanator has been soaked in a 5 % salt water solution at 45 °C for 48 hours.



Quick screw couplings			QSC: QSC	Female thread (DKR)		M (AGR)
M22 : M22	M22 : M22	M22 : M22	M22 : M22 swivel	1/2" : 1/2"	1/2" : 1/2"	3/8" : 3/8"
Nipple & crimp VA	Stainless steel	Zinc-plated steel	Nipple & crimp VA	Stainless steel	Zinc-plated steel	Stainless steel

### Hoses with double wire braid made out of zinc-plated steel and wrapped cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	
Galvanator	10	350 bar	121 °C	10 m	359 100 410 7	359 100 410 9	359 100 410	359 101 410 7	359 156 410 9	359 156 410	359 144 410 9	
					15 m	359 100 415 7	359 100 415 9	359 100 415	359 101 415 7	359 156 415 9	359 156 415	359 144 415 9
					20 m	359 100 420 7	359 100 420 9	359 100 420	359 101 420 7	359 156 420 9	359 156 420	359 144 420 9
					25 m	359 100 425 7	359 100 425 9	359 100 425	359 101 425 7	359 156 425 9	359 156 425	359 144 425 9
					30 m	359 100 430 7	359 100 430 9	359 100 430	359 101 430 7	359 156 430 9	359 156 430	359 144 430 9
				35 m	359 100 435 7	359 100 435 9	359 100 435	359 101 435 7	359 156 435 9	359 156 435	359 144 435 9	
					40 m	359 100 440 7	359 100 440 9	359 100 440	359 101 440 7	359 156 440 9	359 156 440	359 144 440 9

## Food hoses

- » Interior synthetic rubber. Very temperature-resistant. Resistant to usual detergents.
- » Surface special synthetic rubber. Non marking (soot free). Resistant to animal fats.
- » **Field of application:** slaughterhouses, fishing, bakeries etc. Not suitable for swimming baths, poultry fat, standard and industrial cleaning applications.

Quick screw couplings		
M22 : M22	M22 : M22	M22 : M22
Nipple & crimp VA	Stainless steel	Zinc-pl. steel

Other lengths or connections are available on request.

### Hoses with double wire braid and wrapped cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.
2SC	8	400 bar	150 °C	10 m	349 100 410 7	349 100 410 9	349 100 410
				15 m	349 100 415 7	349 100 415 9	349 100 415
				20 m	349 100 420 7	349 100 420 9	349 100 420
2SC	10	400 bar	150 °C	10 m	381 100 410 7	381 100 410 9	381 100 410
				15 m	381 100 415 7	381 100 415 9	381 100 415
				20 m	381 100 420 7	381 100 420 9	381 100 420

All fittings are made out of zinc-plated steel. The hoses are also available with stainless steel fittings.

Please be so kind as to state the following on your order: R+M Nr. plus number:

7 = plug and crimp stainless steel 8 = plug stainless steel 9 = plug, crimp and connection stainless steel

Symbols DN nominal diameter P pressure °C temperature ↔ length TYP type BP burst pressure