

PURClean365+® - food hose

PURClean365+® 40

Female thread DKR 1/2"

Male thread (AGR) 1/2"

Female thread DKR 1/2"

Male thread (AGR) 1/2"

-20 °C - +70 °C. Fittings stainless steel

-20 °C - +70 °C. Fittings stainless steel



R+M Nr.	↔
476 456 202 59	2.5 m
476 456 210 9	10.0 m
476 456 215 9	15.0 m
476 456 220 9	20.0 m
476 456 225 9	25.0 m
476 456 230 9	30.0 m
476 456 235 9	35.0 m
476 456 240 9	40.0 m

R+M Nr.	↔
476 446 202 59	2.5 m
476 446 210 9	10.0 m
476 446 215 9	15.0 m
476 446 220 9	20.0 m
476 446 225 9	25.0 m
476 446 230 9	30.0 m
476 446 235 9	35.0 m
476 446 240 9	40.0 m

R+M Nr.	↔
476 256 702 59	2.5 m
476 256 710 9	10.0 m
476 256 715 9	15.0 m
476 256 720 9	20.0 m
476 256 725 9	25.0 m
476 256 730 9	30.0 m
476 256 735 9	35.0 m
476 256 740 9	40.0 m

R+M Nr.	↔
476 246 702 59	2.5 m
476 246 710 9	10.0 m
476 246 715 9	15.0 m
476 246 720 9	20.0 m
476 246 725 9	25.0 m
476 246 730 9	30.0 m
476 246 735 9	35.0 m
476 246 740 9	40.0 m




PURClean365+® 40 per metre

PURClean365+® 40 per metre

R+M Nr.	DN	↔	↶	P 20 °C	P 70 °C	BP 20 °C	⊞
303 660 42	12	10 - 100 m	4.5	100 bar	45 bar	≥ 250 bar	0.25 kg

R+M Nr.	DN	↔	↶	P 20 °C	P 70 °C	BP 20 °C	⊞
303 660 43	12	10 - 100 m	4.5	100 bar	45 bar	≥ 250 bar	0.25 kg

Screw fittings for PURClean365+®



1/2" M with 60° cone. Stainless steel.
Max. 50 bar

1/2" F with 60° cone. Stainless steel.
Max. 50 bar

1/2" F. Stainless steel. Max. 50 bar. Flat sealing

R+M Nr.	DN
329 412 129	12

R+M Nr.	DN
329 512 129	12

R+M Nr.	DN
329 612 129	12