

Ultra high pressure hoses

Hoses with double wire braid and wrapped cover. Type 2SC. Nominal diameter 10. Safety factor 3.5. Fittings stainless steel. Max. 150 °C

Female thread (DKOS)		Male thread (AGR)		Quick screw couplings	
M22 : M22	M22 : M22	3/8" : 3/8"	3/8" : 3/8"	M22 : M22	M22 : M22
maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar	maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar	maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar
R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
358 177 310 9 10 m	364 177 310 9 10 m	358 144 310 9 10 m	364 144 310 9 10 m	358 100 310 9 10 m	364 100 310 9 10 m
358 177 315 9 15 m	364 177 315 9 15 m	358 144 315 9 15 m	364 144 315 9 15 m	358 100 315 9 15 m	364 100 315 9 15 m
358 177 320 9 20 m	364 177 320 9 20 m	358 144 320 9 20 m	364 144 320 9 20 m	358 100 320 9 20 m	364 100 320 9 20 m
358 177 330 9 30 m	364 177 330 9 30 m	358 144 330 9 30 m	364 144 330 9 30 m	358 100 330 9 30 m	364 100 330 9 30 m

Hoses with double wire braid and wrapped cover. Nominal diameter 10. Fittings stainless steel. Max. 150 °C

Quick screw couplings		
M24 : M24	M24 : M24	M24 : M24
maxpressure. 2SC. Max. 500 bar	2SC. Max. 500 bar	2SN. Max. 600 bar
R+M Nr.	R+M Nr.	R+M Nr.
358 197 310 9 10 m	364 197 310 9 10 m	368 697 610 9 10 m
358 197 315 9 15 m	364 197 315 9 15 m	368 697 615 9 15 m
358 197 320 9 20 m	364 197 320 9 20 m	368 697 620 9 20 m
358 197 330 9 30 m	364 197 330 9 30 m	368 697 630 9 30 m

Hoses with double wire braid and smooth cover. Nominal diameter 6. Fittings stainless steel. Max. 150 °C

Quick screw couplings / male thread (AGR)		
M22 : M22	M22 : 1/8"	1/4" : 1/4"
maxpressure. flexy 500. Max. 500 bar	flexy 500. Max. 500 bar	flexy 500. Max. 500 bar
R+M Nr.	R+M Nr.	R+M Nr.
338 000 310 9 10 m	424 300 010 9 10 m	424 344 010 9 10 m
338 000 315 9 15 m	424 300 015 9 15 m	424 344 015 9 15 m
338 000 320 9 20 m	424 300 020 9 20 m	424 344 020 9 20 m
338 000 330 9 30 m	424 300 030 9 30 m	424 344 030 9 30 m

High pressure hoses

Quick screw couplings		
M22 : M22	M22 : M22 plug VA	M22 : M22 swivel
<i>suitable system 2000</i>		

Hoses with single wire braid and wrapped cover

TYP	DN	P	°C		R+M Nr.	R+M Nr.	R+M Nr.
1SN	8	315 bar	150 °C		344 100 710	344 100 710 8	344 101 710
					344 100 715	344 100 715 8	344 101 715
					344 100 720	344 100 720 8	344 101 720