

## PURClean365+® Power and 150 - food hose

### PURClean365+® Power DN 8

- » PURClean365+® Power - Food hose according to (EC) 1935/2004, (EC) 10/2011 and (EC) 2023/2006.
- » 3-layer plastic hose with a smooth cover.
- » Particularly pressure-stable and flexible up to a maximum of 200 bar working pressure.
- » Area of application: high-pressure cleaning hose in the food industry.
- » Suitable for water and water mixes of usual cleaning detergents.
- » Suitable for contact with liquid food products
- » Increased 1-layer rot-proof textile mesh.

-40 °C - +60 °C. Fittings stainless steel

Female thread DKR 3/8"	Male thread AGR 3/8"	M22 Quick screw couplings
		
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
478 054 610 9 10.0 m	478 044 610 9 10.0 m	478 000 610 9 10.0 m
478 054 615 9 15.0 m	478 044 615 9 15.0 m	478 000 615 9 15.0 m
478 054 620 9 20.0 m	478 044 620 9 20.0 m	478 000 620 9 20.0 m
478 054 625 9 25.0 m	478 044 625 9 25.0 m	478 000 625 9 25.0 m



### PURClean365+® Power per metre

R+M Nr.	DN			P	BP	Ø	⊞
303 672 00	8	100 m	3.8 mm	200 bar	>800 bar	15.3 mm	0.15 kg

### PURClean365+® 150, DN 11

- » PURClean365+® 150 - Food hose according to (EC) 1935/2004, (EC) 10/2011 and (EC) 2023/2006.
- » 3-layer plastic hose with a smooth cover.
- » Particularly pressure-stable and flexible up to a maximum of 150 bar working pressure.
- » Area of application: high-pressure cleaning hose in the food industry, also suitable for foam and spray cleaning.
- » Suitable for water and water mixes of usual cleaning detergents.
- » Suitable for contact with liquid food products
- » Increased 1-layer rot-proof textile mesh.

-40 °C - +60 °C. Fittings stainless steel

Female thread DKR 1/2"	DKR 1/2" : AGR 1/2"	Male thread (AGR) 1/2"	Female thread DKR 3/8"	DKR 3/8" : AGR 3/8"	Male thread (AGR) 3/8"
					
<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 	<b>R+M Nr.</b> 
479 056 602 59 2.5 m	479 057 602 59 2.5 m	479 046 602 59 2.5 m	479 054 602 59 2.5 m	479 055 602 59 2.5 m	479 044 602 59 2.5 m
479 056 610 9 10.0 m	479 057 610 9 10.0 m	479 046 610 9 10.0 m	479 054 610 9 10.0 m	479 055 610 9 10.0 m	479 044 610 9 10.0 m
479 056 615 9 15.0 m	479 057 615 9 15.0 m	479 046 615 9 15.0 m	479 054 615 9 15.0 m	479 055 615 9 15.0 m	479 044 615 9 15.0 m
479 056 620 9 20.0 m	479 057 620 9 20.0 m	479 046 620 9 20.0 m	479 054 620 9 20.0 m	479 055 620 9 20.0 m	479 044 620 9 20.0 m
479 056 625 9 25.0 m	479 057 625 9 25.0 m	479 046 625 9 25.0 m	479 054 625 9 25.0 m	479 055 625 9 25.0 m	479 044 625 9 25.0 m
479 056 630 9 30.0 m	479 057 630 9 30.0 m	479 046 630 9 30.0 m	479 054 630 9 30.0 m	479 055 630 9 30.0 m	479 044 630 9 30.0 m
479 056 635 9 35.0 m	479 057 635 9 35.0 m	479 046 635 9 35.0 m	479 054 635 9 35.0 m	479 055 635 9 35.0 m	479 044 635 9 35.0 m
479 056 640 9 40.0 m	479 057 640 9 40.0 m	479 046 640 9 40.0 m	479 054 640 9 40.0 m	479 055 640 9 40.0 m	479 044 640 9 40.0 m



### PURClean365+® 150 per metre

R+M Nr.	DN			P	BP	Ø	⊞
303 681 50	11	100 m	5.0 mm	150 bar	>550 bar	20.5 mm	0.27 kg