

## Food high pressure hoses per metre

- » Food hose according to (EC)2002/72, (EU) 10/2011, (EG) 1935/2004 and (EG) 2023/2006.
- » Especially designed for industrial foam cleaning applications
- » Fivefold coated PVC hose with a flush surface
- » **Twofold textile meshwork**
- » Suitable for: water and water mixes of usual cleaning detergents

### blufood®



**Field of application:** foam hose and pre-spraying hose for the food industry.  
**Suitable for the contact with liquid food products**

| R+M Nr.     | TYP     | DN | ∅  | P 20 °C | P 70 °C | BP 20 °C  | °C              |
|-------------|---------|----|----|---------|---------|-----------|-----------------|
| 303 70      | blufood | 12 | 22 | 50 bar  | 30 bar  | ≥ 240 bar | -20 °C - +70 °C |
| 303 700 019 | blufood | 19 | 31 | 40 bar  | 15 bar  | ≥ 200 bar | -20 °C - +70 °C |

## Food high pressure hoses per metre

### Foodjet



- » Food hose EN 854
- » **Particularly resistant to animal and poultry fats**
- » Surface synthetic rubber
- » **Interior synthetic, oil-resistant rubber**
- » **2 tight textile meshwork**
- » Suitable for: oil, water, water-in-oil emulsion and water mixes with up to 50 % detergent
- » Particularly abrasion-, oil-, ozone-resistant, weatherproof and food safe

**Field of application:** cleaning hose designed for the food industry.

| R+M Nr. | TYP     | DN | ∅    | P      | BP  | °C               |
|---------|---------|----|------|--------|-----|------------------|
| 303 60  | Foodjet | 12 | 19.7 | 80 bar | 240 | -40 °C - +150 °C |

### greyflex



- » Especially developed to meet highest requirements to hygiene and ergonomics
- » Smooth surface made out of thermoplastic elastomer
- » **Brass-plated wire braid, fabric braid, high-tensile polyester meshwork and PES-interior very resistant to detergents**
- » Suitable for: oil, water, water-oil emulsion and water-detergent mixture.
- » Particularly abrasion-, UV-, grease-, oil-, ozone-resistant and weatherproof
- » extremely light weight and flexible in case of low temperatures
- » Roll at 100 m

**Field of application:** Food and beverage industry, fish farming and swimming pools

| R+M Nr.     | TYP      | DN | ∅    | P       | BP    | °C               |
|-------------|----------|----|------|---------|-------|------------------|
| 300 201 110 | greyflex | 10 | 17.4 | 275 bar | 1,100 | -40 °C - +120 °C |

### easyfarm365+



- » Especially developed for the use in the agriculture
- » Excellent ease of use and high safety
- » Smooth transparent surface made out of thermoplastic elastomer
- » **Brass-plated wire braid, fabric braid, high-tensile polyester meshwork and PES-interior very resistant to detergents**
- » Suitable for: oil, water, water-oil emulsion and water-detergent mixture
- » Particularly abrasion-, UV-, oil-, ozone-resistant and weatherproof
- » Ideal for the use on rough floors under hardest conditions
- » Roll at 100 m

**Field of application:** Professional cot and machine cleaning in the agriculture

| R+M Nr.     | TYP          | DN | ∅    | P       | BP    | °C               |
|-------------|--------------|----|------|---------|-------|------------------|
| 300 201 408 | easyfarm365+ | 8  | 15.1 | 250 bar | 1,000 | -40 °C - +120 °C |
| 300 201 410 | easyfarm365+ | 10 | 17.4 | 275 bar | 1,100 | -40 °C - +120 °C |
| 300 201 412 | easyfarm365+ | 12 | 20.8 | 180 bar | 720   | -40 °C - +120 °C |

**Symbols** DN nominal diameter ∅ diameter TYP type P pressure BP burst pressure °C temperature