

High pressure hoses per metre

Plastic



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|---------|-------|----|-----|---------|----------|----------------|
| 304 01 | black | 5 | 9.9 | 120 bar | ≥440 bar | -20 °C - 60 °C |



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|---------|-------|----|------|---------|----------|----------------|
| 304 10 | black | 5 | 10.4 | 200 bar | ≥800 bar | -30 °C - 60 °C |



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|---------|-------|----|------|---------|----------|----------------|
| 300 01 | black | 6 | 11.6 | 160 bar | ≥640 bar | -20 °C - 65 °C |

blupur



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|---------|--------|----|------|---------|----------|----------------|
| 304 15 | blupur | 5 | 10.3 | 200 bar | ≥800 bar | -40 °C - 60 °C |

R+M 1 / Bronze



- » Interior polyester / elastomer
- » Very elastic version
- » Single wire braid
- » Surface polyurethane

Field of application: Semi-professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|---------|-------|----|-----|---------|-------------|-----------------|
| 304 20 | R+M 1 | 4 | 9.2 | 300 bar | ≥ 1,000 bar | -40 °C - +98 °C |

Flexy



- » Interior synthetic rubber
- » Very elastic version
- » Single wire braid, * double wire braid
- » Surface synthetic rubber
- » Abrasion-, oil-resistant and weatherproof

Field of application: Professional hp cleaning & pipe cleaning

| R+M Nr. | TYP | DN | Ø | P | BP | °C |
|----------|-----------|----|------|---------|-------------|------------------|
| 300 95 | Flexy 300 | 6 | 10.8 | 300 bar | ≥ 800 bar | -40 °C - +100 °C |
| 300 97 * | Flexy 500 | 6 | 14.5 | 600 bar | ≥ 2,000 bar | -40 °C - +150 °C |

Symbols DN nominal diameter Ø diameter TYP type P pressure BP burst pressure °C temperature