

ST-49 nozzles for sewer cleaning

Sewer cleaning nozzles with male thread



Due to its conical front design this is the ideal solution to make its way through tight bends and traps. Ideal for hobby and semi-professional use. 3 rear jets for maximum thrust. Nozzle drillings as stepped bore for protection against mechanical impact.

Outside \varnothing 15 mm.

Brass.

Max. 210 bar / 16 l/min

R+M Nr.	G	D
121 000 360	1/4" M	035



Due to its conical front design this is the ideal solution to make its way through tight bends and traps. 3 rear jets for maximum thrust and high cleaning impact. Front jet to blast through roots and scale or de-icing. Nozzle drillings as stepped bore for best protection against mechanical impact.

Outside \varnothing 15 mm.

Stainless steel.

Max. 350 bar / 17 l/min

R+M Nr.	G	D
121 160 360	1/4" M	040



Due to its conical front design this is the ideal solution to make its way through tight bends and traps. 8 rear jets for maximum thrust and best wall coverage. Front jet to blast through roots and scale or de-icing. Nozzle drillings as stepped bore for best protection against mechanical impact. 3 rear jets for maximum thrust and best wall coverage.

Outside \varnothing 15 mm.

Stainless steel.

Max. 350 bar / 25 l/min

R+M Nr.	G	D
123 160 860	3/8" M	060



Compact and heavy construction with 3 rear jets. For standard cleaning and desilting applications. Outside \varnothing 25 mm. Stainless steel.

Max. 500 bar / 40 l/min

R+M Nr.	G	D
120 000 312	1/2" M	080



Drain cleaning nozzle suitable for use on most van and trailer mounted cleaning machines. 4 rear jets (30°) for higher thrust. Conical head for tight bends and offsets. Outside \varnothing 24.2 mm. Stainless steel.

Max. 500 bar / 45 l/min

R+M Nr.	G	D
120 110 410	1/2" M	090

Sewer cleaning nozzles with female thread



Due to its very compact design this is the ideal solution for tight elbows. 6 rear jets for maximum thrust and best wall coverage.

Outside \varnothing 22 mm.

Hardened stainless steel.

Max. 500 bar / 30 l/min

R+M Nr.	G	D
120 000 675	1/4" F	060



Due to its very compact design this is the ideal solution for tight elbows. 3 rear jets for maximum thrust and powerful cleaning impact.

Front jet to blast through roots and scale or de-icing.

Outside \varnothing 15 mm.

Hardened stainless steel.

Max. 500 bar / 17 l/min

R+M Nr.	G	D
120 155 375	1/8" F	035



Due to its conical front design this is the ideal solution to make its way through tight bends and traps.

3 rear jets for maximum thrust and powerful cleaning impact.

Front jet to blast through roots and scale or de-icing.

Outside \varnothing 22 mm.

Hardened stainless steel.

Max. 500 bar / 25 l/min

R+M Nr.	G	D
120 163 390	1/4" F	045



Due to its very compact design this is the ideal solution for tight elbows. 3 rear jets for maximum thrust and powerful cleaning impact.

Front jet to blast through roots and scale or de-icing.

Outside \varnothing 22 mm.

Hardened stainless steel.

Max. 500 bar / 30 l/min.

R+M Nr.	G	D
120 163 391	1/4" F	050