













## Autres raccords à sertir spécialisés

### Embout à sertir

																																			
																																			
Coupleur. Acier zingué. Type 03 & 04	Coupleur. Laiton. Type 03	Coupleur. Acier zingué. Type 03 & 04	Rotatif Ø 10 mm. Inox. Type 03 & 04	Rotatif Ø 11 mm. Inox. Type 03 & 04	Rotatif Ø 11 mm. Acier zingué. Type 03 & 04																														
R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 95</td><td>6</td></tr><tr><td>316 98</td><td>8</td></tr></table>	DN		316 95	6	316 98	8	R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 951 6</td><td>6</td></tr></table>	DN		316 951 6	6	R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 951 8</td><td>6</td></tr></table>	DN		316 951 8	6	R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 93</td><td>6</td></tr></table>	DN		316 93	6	R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 94</td><td>6</td></tr><tr><td>316 96</td><td>8</td></tr><tr><td>316 961 0</td><td>10</td></tr></table>	DN		316 94	6	316 96	8	316 961 0	10	R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>316 961</td><td>8</td></tr></table>	DN		316 961	8
DN																																			
316 95	6																																		
316 98	8																																		
DN																																			
316 951 6	6																																		
DN																																			
316 951 8	6																																		
DN																																			
316 93	6																																		
DN																																			
316 94	6																																		
316 96	8																																		
316 961 0	10																																		
DN																																			
316 961	8																																		

## Embout femelles et joints pour coupleurs et raccords manuels

Embout à sertir femelles	Joints de rechange					Kit joints ST-44																									
	1/4" F. Inox																														
R+M Nr. <table border="1"><tr><th>DN</th><th></th></tr><tr><td>314 79</td><td>6</td></tr><tr><td>314 89</td><td>8</td></tr><tr><td>314 99</td><td>10</td></tr></table>	DN		314 79	6	314 89	8	314 99	10	Joint torique. Type 01	Joint torique. Viton. Type 02	Joint torique. Type 03	Anti-extrusion. Type 04	Joint torique. Type 05	R+M Nr. <table border="1"><tr><td>568 001 1</td></tr></table>	568 001 1																
DN																															
314 79	6																														
314 89	8																														
314 99	10																														
568 001 1																															
	R+M Nr. <table border="1"><tr><th>VPE</th><th></th></tr><tr><td>790 10</td><td>1</td></tr><tr><td>790 100</td><td>100</td></tr></table>	VPE		790 10	1	790 100	100	R+M Nr. <table border="1"><tr><th>VPE</th><th></th></tr><tr><td>790 20</td><td>1</td></tr><tr><td>790 201 00</td><td>100</td></tr></table>	VPE		790 20	1	790 201 00	100	R+M Nr. <table border="1"><tr><th>TYP</th><th></th></tr><tr><td>790 55</td><td>10 mm</td></tr><tr><td>790 57</td><td>11 mm</td></tr></table>	TYP		790 55	10 mm	790 57	11 mm	R+M Nr. <table border="1"><tr><th>TYP</th><th></th></tr><tr><td>790 58</td><td>10 mm</td></tr><tr><td>790 59</td><td>11 mm</td></tr></table>	TYP		790 58	10 mm	790 59	11 mm	R+M Nr. <table border="1"><tr><td>791 032 4</td></tr></table>	791 032 4	
VPE																															
790 10	1																														
790 100	100																														
VPE																															
790 20	1																														
790 201 00	100																														
TYP																															
790 55	10 mm																														
790 57	11 mm																														
TYP																															
790 58	10 mm																														
790 59	11 mm																														
791 032 4																															

## Écrous pour raccords manuels











### Écrous inox pour embouts à sertir

» M22 F.  
» Max. 500 bar

																									
	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 209</td><td>16,4</td></tr></table>	Ø		319 209	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 219</td><td>16,4</td></tr></table>	Ø		319 219	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 269</td><td>16,4</td></tr></table>	Ø		319 269	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 259</td><td>16,4</td></tr></table>	Ø		319 259	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>040 000 824</td><td>16,4</td></tr></table>	Ø		040 000 824	16,4
Ø																									
319 209	16,4																								
Ø																									
319 219	16,4																								
Ø																									
319 269	16,4																								
Ø																									
319 259	16,4																								
Ø																									
040 000 824	16,4																								

### Écrous laiton pour embouts à sertir

» Max. 400 bar

																									
	M22 F	M22 F	M22 F	M22 F	M22 F.																				
	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 20</td><td>16,4</td></tr></table>	Ø		319 20	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 21</td><td>16,4</td></tr></table>	Ø		319 21	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 26</td><td>16,4</td></tr></table>	Ø		319 26	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 25</td><td>16,4</td></tr></table>	Ø		319 25	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>010 000 721</td><td>16,4</td></tr></table>	Ø		010 000 721	16,4
Ø																									
319 20	16,4																								
Ø																									
319 21	16,4																								
Ø																									
319 26	16,4																								
Ø																									
319 25	16,4																								
Ø																									
010 000 721	16,4																								
																									
	M22 F	M21 F	M21 F	M22 F																					
	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 201</td><td>17,3</td></tr></table>	Ø		319 201	17,3	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>200 042 154</td><td>16,4</td></tr></table>	Ø		200 042 154	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 10</td><td>16,4</td></tr></table>	Ø		319 10	16,4	R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 231</td><td>17,3</td></tr></table>	Ø		319 231	17,3					
Ø																									
319 201	17,3																								
Ø																									
200 042 154	16,4																								
Ø																									
319 10	16,4																								
Ø																									
319 231	17,3																								

### Écrous acier zingué pour embouts à sertir

» Max. 400 bar

	M22 x 1,5 F				
R+M Nr. <table border="1"><tr><th>Ø</th><th></th></tr><tr><td>319 28</td><td>16,3</td></tr></table>	Ø		319 28	16,3	
Ø					
319 28	16,3				