

Milling Type Nozzles ST-49

With its 3 to 4 very strong concentrated forward jets and the sharp cutting edges the milling type nozzles will tear through almost any kind of blockage. The sharp edges cut, break and penetrate through every kind of blockage. Made out of wear-resistant, hardened stainless steel. All nozzles are equipped with replaceable hardened stainless steel rear and

centric front jets. Due to this feature the efficiency is considerably higher compared to those nozzles with drilled holes and the service life is several times longer. Max. 300 / 350 bar

Applications:

- » Penetration of completely clogged pipes
- » Opening of root masses
- » Opening of frozen pipelines
- » Hydraulic thrust boring flushing operations



350 bar. 1/4" F. For tubes > 30 mm.
Lateral front jets 0.5 mm drilled



350 bar. 3/8" F. For tubes > 50 mm.
Lateral front jets with hardened stainless steel nozzle inserts



R+M Nr.	⌀	Front	Rear
649 010 234 045	045	3	4
649 010 234 050	050	3	4
649 010 234 055	055	3	4
649 010 244 060	060	4	4
649 010 244 070	070	4	4
649 010 244 080	080	4	4
649 010 244 085	085	4	4
649 010 244 100	100	4	4
649 010 244 120	120	4	4
649 010 244 150	150	4	4
649 010 244 200	200	4	4

R+M Nr.	⌀	Front	Rear
649 010 336 055	055	3	6
649 010 346 070	070	4	6
649 010 346 080	080	4	6
649 010 346 100	100	4	6
649 010 346 120	120	4	6
649 010 346 150	150	4	6
649 010 346 200	200	4	6
649 010 346 250	250	4	6
649 010 346 270	270	4	6



350 bar. 1/2" F. For tubes > 60 mm
Lateral front jets with hardened stainless steel nozzle inserts



300 bar. 3/4" F. For tubes > 60 mm
Lateral front jets with hardened stainless steel nozzle inserts

R+M Nr.	⌀	Front	Rear
649 010 446 100	100	4	6
649 010 446 120	120	4	6
649 010 446 150	150	4	6
649 010 446 200	200	4	6
649 010 446 250	250	4	6
649 010 446 270	270	4	6
649 010 446 310	310	4	6
649 010 446 495	495	4	6
649 010 446 580	580	4	6

R+M Nr.	⌀	Front	Rear
649 010 546 120	120	4	6
649 010 546 150	150	4	6
649 010 546 180	180	4	6
649 010 546 200	200	4	6
649 010 546 250	250	4	6
649 010 546 270	270	4	6
649 010 546 310	310	4	6
649 010 546 450	450	4	6
649 010 546 495	495	4	6