

Sewer cleaning hose assemblies

sewerclean365+ PU-sewer cleaning hose

- » cut- and abrasion-resistant
- » extremely long operating life
- » highly tearproof by two-fold braid of aramid fibres and polyurethane surface
- » good swimming features
- » ageing resistant and weather-resistant surface
- » -40 °C - +60 °C, -40 °F - +140 °F



DKR : M

1/2" : 1/2"



All hoses are supplied together with a test certificate according to EN 10204.3.1.1.

DN	P	⊙	⊘	BP	↔
12	275 bar	12.7 mm	23.4 mm	840 bar	40 m
					60 m
					80 m
					100 m
					120 m

R+M Nr.
432 457 120 040
432 457 120 060
432 457 120 080
432 457 120 100
432 457 120 120

sewerstar365+ Gummi-Kanalspülschläuche

- » highly abrasion-resistant with an extremely long operating life
- » high flexibility by especially developed rubber compound
- » extremely abrasion-resistant, ageing resistant and weather-resistant surface
- » easy handling by low weight
- » excellent pressure resistance and tensile strength
- » very low bending radius
- » wire braid for high stability
- » interior and surface are made out of NR/SBR
- » -40 °C - +150 °C, -40 °F - +302 °F



DKR : M

1/2" : 1/2"



3/8" : 3/8"



3/8" : 1/4"



DN	P	⊙	⊘	BP	↔
08	500 bar	7.9 mm	15.0 mm	1260 bar	40 m
					80 m
10	280 bar	9.8 mm	16.9 mm	740 bar	40 m
					60 m
					80 m
					100 m
					120 m
12	250 bar	12.7 mm	22.6 mm	640 bar	40 m
					60 m
					80 m
					100 m
					120 m

R+M Nr.
432 557 100 040
432 557 100 060
432 557 100 080
432 557 100 100
432 557 100 120
432 557 120 040
432 557 120 060
432 557 120 080
432 557 120 100
432 557 120 120

R+M Nr.
432 558 080 040
432 558 080 080
432 558 100 040
432 558 100 060
432 558 100 080
432 558 100 100
432 558 100 120

R+M Nr.
432 556 080 040
432 556 080 080

Symbols DN nominal diameter ⊙ internal diameter ⊘ diameter P pressure BP burst pressure °C temperature shipment by truck