

ST-49 Ball type nozzle, 20°

Made out of stainless steel provided with front jet insert or blind plug (interchangeable). Angle of jet is 20°, sturdy wall thickness, long service life and a minimum of wear and tear. All nozzles are provided with hardened stainless steel inserts. Due to this feature the efficiency is considerably

higher compared with those nozzles with drilled holes and the service life is several times longer.
Max. 500 bar

Applications:

- » Suitable for removal of sludge deposits
- » Desilting of pipes
- » Opening of frozen pipelines



1/4" F.
Outside \varnothing 25 mm.
rear jets

R+M Nr.	D	rear jets
649 090 206 060	060	6
649 090 206 080	080	6
649 090 206 100	105	6
649 090 206 120	120	6
649 090 206 160	160	6
649 090 206 200	200	6



1/4" F.
Outside \varnothing 25 mm.
rear jets, with front jet

R+M Nr.	D	rear jets
649 090 216 060	060	6
649 090 216 080	080	6
649 090 216 100	100	6
649 090 216 120	120	6
649 090 216 150	150	6
649 090 216 200	200	6



3/8" F.
Outside \varnothing 30 mm.
rear jets

R+M Nr.	D	rear jets
649 090 306 060	060	6
649 090 306 080	080	6
649 090 306 100	105	6
649 090 306 120	120	6
649 090 306 160	160	6
649 090 306 200	200	6



3/8" F.
Outside \varnothing 30 mm.
rear jets, with front jet

R+M Nr.	D	rear jets
649 090 316 060	060	6
649 090 316 080	080	6
649 090 316 100	100	6
649 090 316 120	120	6
649 090 316 150	150	6
649 090 316 200	200	6

Jet angle INFO

30°

30° = more efficient wall cleaning

20°

20° = better traction