

## Suttner high pressure spray guns

ST-2315



Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stain. steel seal seat. Designed for applications e.g. in the prewash of vehicles.  
Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 315 500	1/4" F	3/8" F

ST-2600



**LTF**

Professional gun with patented LTF technology.  
Max. 310 bar / 45 l/min / 150 °C

R+M Nr.		
202 600 560	1/4" F	3/8" F

ST-2605



**LTF**

Professional gun with patented LTF technology.  
Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 605 500	1/4" F	3/8" F stainless steel

ST-2615



**LTF**

Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel seal seat. Designed for applications e.g. in the prewash of vehicles.  
Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 500	1/4" F	3/8" F



**LTF**

Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel seal seat. Designed for applications e.g. in the prewash of vehicles.  
Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 550	1/4" F	3/8" F swivel

### Valves complete



ST-2315, ST-2615

R+M Nr.
202 315 490



ST-2600

R+M Nr.
202 300 490



ST-2605

R+M Nr.
202 300 492



ST-2635 Industrial

R+M Nr.
202 300 492



easyfarm365+

R+M Nr.
202 620 491

### ST-311 swivel



1/4" F : 3/8" F

R+M Nr.
200 311 050



1/4" F : M22 M

R+M Nr.
200 311 060



Repair kit ST-311

R+M Nr.
200 300 100

Symbols outlet inlet

**LTF - Low Trigger Force** 90 % reduced holding force and 40 % reduced trigger force against usual market guns.

**LTF+ - Low Trigger Force +** 90 % reduced holding force and 55 % reduced trigger force against usual market guns.