



## Suttner Hochdruckspritzpistolen

## ST-810





Max. 210 bar / 30 l/min / 150 °C

|                |   |   |
|----------------|---|---|
| <b>R+M Nr.</b> |  |  |
| 200 810 740    | M22 AG  | M22 AG  |



IP Kr

Pistole ST-810 mit Verlängerung 340 mm und HV M22. Max. 210 bar / 30 l/min / 150 °C

|                |   |   |
|----------------|---|---|
| <b>R+M Nr.</b> |  |  |
| 200 810 750    | HV M22  | M22 AG  |



Max. 210 bar / 30 l/min / 150 °C

|                |   |   |
|----------------|---|---|
| <b>R+M Nr.</b> |  |  |
| 200 810 530    | 1/4" IG   | 1/4" IG   |

## ST-810



Ventil komplett

|                |
|----------------|
| <b>R+M Nr.</b> |
| 200 810 491    |

## ST-860



Pistole mit PEEK Sitz.



Max. 210 bar / 30 l/min / 100 °C

|                |   |   |
|----------------|---|---|
| <b>R+M Nr.</b> |  |  |
| 200 860 500    | 1/4" IG   | 1/4" IG   |



Pistole mit PEEK Sitz.

Max. 210 bar / 30 l/min / 100 °C




|                |   |   |
|----------------|---|---|
| <b>R+M Nr.</b> |  |  |
| 200 860 520    | M22 AG  | M22 AG  |

## ST-860



Ventil komplett

|                |
|----------------|
| <b>R+M Nr.</b> |
| 200 860 490    |

Symbole  Ausgang  Eingang  Länge