

## Low pressure hoses

## Rubber hoses black



Black surface and interior. Industrial version for water and compressed air. Abrasion- and ozone-resistant. Burst pressure > 60 bar. Max. 20 bar. -10 °C - +60 °C

## Per metre

R+M Nr.	DN	↔	↗
305 10	13 (1/2")		4
305 20	19 (3/4")		5
305 30	25 (1")		5

## Complete rolls \*

R+M Nr.	DN	↔	↗
305 101 00	13 (1/2")	100 m	4
305 201 00	19 (3/4")	100 m	5
305 301 00	25 (1")	100 m	5

## Reinforced PVC hoses clear



Clear. Max. 60 °C. Other dimensions are available on request

## Per metre

R+M Nr.	DN	↗
306 40	6	3.0
306 50	8	3.0
306 55	9	3.0
306 60	10	3.0
307 10	12	3.0
306 70	13	3.0
306 80	16	3.0
306 90	19	3.5

## Complete rolls

R+M Nr.	DN	↔	↗
306 401 00	6	100 m	3.0
306 501 00	8	100 m	3.0
306 550 50	9	50 m	3.0
306 600 50	10	50 m	3.0
307 100 50	12	50 m	3.0
306 700 50	13	50 m	3.0
306 800 50	16	50 m	3.0
306 900 50	19	50 m	3.5

## Rubber hoses grey



Grey NBR surface. White, food safe interior. Suitable for hot and cold liquids. Resistant to animal fats. Burst pressure > 60 bar. Max. 20 bar. -20 °C - +100 °C

## Per metre

R+M Nr.	DN	↗
305 40	13 (1/2")	4.5
305 50	19 (3/4")	4.8

## Spiral line hoses



Especially for suction. Suitable for vacuum. -10 °C - +50 °C


## Per metre

R+M Nr.	DN	↗
307 519	19 (3/4")	2.6
307 525	25 (1")	2.7
307 532	32 (1.1/4")	2.7
307 538	38 (1.1/2")	2.7
307 550	50 (2")	4.0

## Complete rolls

R+M Nr.	DN	↔	↗
307 519 025	19 (3/4")	25 m	2.6
307 525 025	25 (1")	25 m	2.7
307 532 025	32 (1.1/4")	25 m	2.7
307 538 025	38 (1.1/2")	25 m	2.7
307 550 025	50 (2")	25 m	4.0

## Reinforced PVC hoses blue



Max. 60 °C. Other dimensions are available on request

## Per metre

R+M Nr.	DN	↗
080 000 310	9	3
306 71	13	3

## Complete rolls

R+M Nr.	DN	↔	↗
306 560 50	9	50 m	3
306 710 50	13	50 m	3

## Plastic hoses yellow



NTS WHITE PLUS. Yellow surface with blue stripes. White interior. Food safe. PVC water hose with six layers. Abrasion- /UV-resistant. Lead and cadmium free. Phthalate free. Food safe.

Burst pressure > 30 bar. -20 °C - +65 °C

## Complete rolls

R+M Nr.	DN	↔	↗
305 112 25	13 (1/2")	25 m	2.3
305 112 50	13 (1/2")	50 m	2.3
305 134 25	19 (3/4")	25 m	2.8
305 134 50	19 (3/4")	50 m	2.8

## Clear PVC hoses



Especially for suction of chemicals. Max. 60 °C. Other dimensions are available on request

## Per metre

R+M Nr.	DN	↗
306 10	4	1.0
306 20	6	1.5
306 30	8	2.0

## Complete rolls

R+M Nr.	DN	↔	↗
306 101 00	4	100 m	1.0
306 201 00	6	100 m	1.5
306 301 00	8	100 m	2.0

## Reinforced PVC hoses yellow



Max. 60 °C. Other dimensions are available on request

## Per metre

R+M Nr.	DN	↗
080 000 300	6	3
080 000 320	9	3

## Complete rolls

R+M Nr.	DN	↔	↗
306 410 50	6	50 m	3
306 570 50	9	50 m	3