

## Suttner Hochdruckspritzpistolen

### ST-1500



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 500	1/4" IG	3/8" IG



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 560	1/4" IG	3/8" IG dreh.



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 550	1/4" IG	M22 AG



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 545	M22 AG	M22 AG



Professionelle Pistole.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 760	HV M22	M22 AG



Professionelle Pistole. Frostschutzausführung.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 580	1/4" IG	3/8" IG



Professionelle Pistole. Frostschutzausführung.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 581	1/4" IG	3/8" IG dreh.



Professionelle Pistole. Weepausführung.  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 620	1/4" IG	3/8" IG



Professionelle Pistole ohne Ventil (Freifluss).  
Max. 275 bar / 45 l/min / 150 °C

<b>R+M Nr.</b>		
201 500 750	1/4" IG	3/8" IG

### ST-300 Drehgelenk



1/4" IG : 3/8" IG. ST-1500

<b>R+M Nr.</b>
200 300 050



Reparatursatz ST-300

<b>R+M Nr.</b>
200 300 100

### Reparatursatz



ST-1100. Drehgelenk

<b>R+M Nr.</b>
200 300 100

### Dichtsatz



ST-1100

<b>R+M Nr.</b>
201 100 401

### Ventile komplett



ST-1500

<b>R+M Nr.</b>
202 000 044



ST-1500 Weep

<b>R+M Nr.</b>
202 000 045



ST-1500 Frostschutz

<b>R+M Nr.</b>
202 000 101

Symbole Ausgang Eingang