

Suttner high pressure spray guns



Spray gun:	ST-860D	ST-4000	ST-1200	ST-1200	ST-3240	ST-3225	ST-3100	ST-2725
Max. pressure	20 bar	20 bar	24 bar	24 bar	310 bar	24,5 / 60 bar	60 bar	80 bar
Max. flow	30 l/min	50 l/min	100 l/min	100 l/min	120 l/min	120 l/min	100 l/min	80 l/min
Max. temperature	200 °C	200 °C	50 °C	50 °C	100 °C	100 °C	150 °C	150 °C
Inlet	front	front	rear	rear	linear	linear	rear	rear
Swivel at inlet	-	-	-	-	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Chemical resistance	very high	-	-	-	high	high	high	high
Freeze stop version	-	-	-	-	-	-	-	-
Weep version	-	<input type="checkbox"/>	-	-	-	-	-	-
LTF technology	-	-	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	-	<input checked="" type="checkbox"/>
Material valve housing	brass	aluminium	brass	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
Material valve	PEEK / brass	PEEK / stainless steel	brass / stainless steel	stainless steel	PEEK / stainless steel	PEEK / stainless steel	PEEK / stainless steel	PEEK / stainless steel
Food safe	-	-	-	-	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
One-piece valve kit	-	-	-	-	-	-	-	-
Quick coupling	-	-	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Quick coupling	-	-	-	-	-	-	-	-
Progressive closing	-	-	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Private label	<input type="checkbox"/>	<input type="checkbox"/>	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Swivel at outlet	-	-	-	-	-	-	-	-
Catalogue page	19 / 214	19 / 214	16	16	224	215, 325, 331, 332	218	217



Spray gun:	ST-2720	ST-810 ND	ST-3300	kommunal365+	ST-810 HD	ST-860	ST-1100	R+M EcoLine ONE
Max. pressure	125 bar	140 bar	150 bar	150 bar	210 bar	210 bar	210 bar	250 bar
Max. flow	80 l/min	30 l/min	100 l/min	80 l/min	30 l/min	30 l/min	25 l/min	45 l/min
Max. temperature	150 °C	80 °C	150 °C	150 °C	150 °C	100 °C	150 °C	150 °C
Inlet	rear	front	rear	rear	front	front	rear	rear
Swivel at inlet	<input type="checkbox"/>	-	<input type="checkbox"/>	<input type="checkbox"/>	-	-	<input type="checkbox"/>	-
Chemical resistance	high	high	high	-	-	high	-	-
Freeze stop version	-	-	-	-	-	-	-	-
Weep version	-	-	-	-	-	-	<input type="checkbox"/>	-
LTF technology	<input checked="" type="checkbox"/>	-	-	-	-	-	-	-
Material valve housing	stainless steel	brass	stainless steel	brass	brass	brass	brass	brass
Material valve	PEEK / stainless steel	POM / stainless steel	stainless steel	brass / stainless steel	stainless steel	PEEK / stainless steel	brass / stainless steel	brass / stainless steel
Food safe	-	-	<input checked="" type="checkbox"/>	-	-	-	-	-
One-piece valve kit	-	-	-	-	-	-	-	<input checked="" type="checkbox"/>
Quick coupling	<input type="checkbox"/>	-	<input type="checkbox"/>	-	-	-	<input type="checkbox"/>	<input type="checkbox"/>
Quick coupling	-	-	-	-	-	-	-	-
Progressive closing	-	-	-	-	-	-	-	-
Private label	<input type="checkbox"/>	-	-	<input type="checkbox"/>	-	<input type="checkbox"/>	-	-
Swivel at outlet	-	-	-	-	-	-	-	-
Catalogue page	216, 217	17, 231	218, 324	223, 481	210	17, 210, 214	211 / 228	213

Symbols standard optional outlet inlet