

Suttner high pressure spray guns

ST-2315



Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the prewash of vehicles.

Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 315 500	1/4" F	3/8" F



Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the prewash of vehicles.

Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 315 550	1/4" F	3/8" F swivel

ST-2600



LTF

Professional gun with patented LTF technology. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.		
202 600 560	1/4" F	3/8" F

ST-2600



LTF

Professional gun with patented LTF technology. Coupling ST-247 stainless steel. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.		
202 600 747	ST-247 swivel	ST-247 swivel

ST-2605



LTF

Professional gun with patented LTF technology. Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 605 500	1/4" F	3/8" F stainless steel

ST-2615



LTF

Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the prewash of vehicles. Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 500	1/4" F	3/8" F

ST-2615



LTF

Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the prewash of vehicles. Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 550	1/4" F	3/8" F swivel



LTF


Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the construction industry, road works or mining. Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 615	1/4" F	3/8" F swivel



LTF

Professional gun. Ceramic ball, chemically resistant valve and acid-resistant stainless steel sealing seat. Designed for applications e.g. in the construction industry, road works or mining. Max. 350 bar / 45 l/min / 150 °C

R+M Nr.		
202 615 525	coupling KW	3/8" F swivel

Symbols  outlet  inlet