

Suttner Hochdruckspritzpistolen

ST-2000



Professionelle Pistole.
Max. 275 bar / 45 l/min / 150 °C

| | | |
|----------------|---------|---------|
| R+M Nr. | | |
| 202 000 500 | 1/4" IG | 3/8" IG |



Professionelle Pistole.
Max. 275 bar / 45 l/min / 150 °C

| | | |
|----------------|---------|---------------|
| R+M Nr. | | |
| 202 000 590 | 1/4" IG | 3/8" IG dreh. |

ST-300 Drehgelenk



1/4" IG : 3/8" IG. ST-2000

| |
|----------------|
| R+M Nr. |
| 200 300 050 |



Reparatursatz ST-300

| |
|----------------|
| R+M Nr. |
| 200 300 100 |

Ventil komplett



ST-2000

| |
|----------------|
| R+M Nr. |
| 202 000 044 |

kommunal365+



Professionelle Pistole.
Max. 150 bar / 80 l/min / 150 °C

| | | |
|----------------|---------|---------|
| R+M Nr. | | |
| 202 320 500 | 1/4" IG | 1/2" IG |



Professionelle Pistole.
Max. 150 bar / 80 l/min / 150 °C

| | | |
|----------------|---------|---------|
| R+M Nr. | | |
| 202 320 510 | 1/2" IG | 1/2" IG |



Professionelle Pistole.
Max. 150 bar / 80 l/min / 150 °C

| | | |
|----------------|---------|---------------|
| R+M Nr. | | |
| 202 320 520 | 1/2" IG | 1/2" IG dreh. |

ST-340 Drehgelenk



1/4" IG : 1/2" IG

| |
|----------------|
| R+M Nr. |
| 200 340 520 |



Reparatursatz ST-340

| |
|----------------|
| R+M Nr. |
| 200 340 100 |

Dichtsatz



| |
|----------------|
| R+M Nr. |
| 202 320 495 |

Schulterstütze



Neue EU-Richtlinien schreiben den Gebrauch von Schulterstützen bei Arbeiten mit einer Rückstoßkraft von mehr als 150 N zwingend vor.

| |
|----------------|
| R+M Nr. |
| 202 705 590 |

Symbole Ausgang Eingang