

Schlauchtüllen

Außengewinde



Messing.  
Max. 150 °C



Edelstahl.  
Max. 150 °C



Kunststoff.  
Max. 60 °C



Kunststoff.  
Max. 60 °C

Innengewinde



Messing.  
Max. 150 °C

| DN    | ⊙    |
|-------|------|
| 4 mm  | 1/8" |
| 6 mm  | 1/8" |
| 6 mm  | 1/4" |
| 6 mm  | 3/8" |
| 6 mm  | 1/2" |
| 7 mm  | 1/8" |
| 8 mm  | 1/4" |
| 8 mm  | 3/8" |
| 8 mm  | 1/2" |
| 9 mm  | 3/8" |
| 9 mm  | 1/2" |
| 10 mm | 1/4" |
| 10 mm | 3/8" |
| 12 mm | 1/4" |
| 12 mm | 3/8" |
| 12 mm | 1/2" |
| 12 mm | 3/4" |
| 16 mm | 1/2" |
| 16 mm | 3/4" |
| 19 mm | 1/2" |
| 19 mm | 3/4" |
| 19 mm | 1"   |
| 25 mm | 3/4" |
| 25 mm | 1"   |

| R+M Nr. | ⊥  |
|---------|----|
| 710 00  | 31 |
| 710 10  | 35 |
| 710 40  | 36 |
| 710 65  | 40 |
| 710 05  | 31 |
| 710 20  | 34 |
| 710 50  | 38 |
| 710 70  | 49 |
| 710 25  | 34 |
| 710 55  | 35 |
| 710 30  | 35 |
| 710 60  | 38 |
| 710 80  | 50 |
| 710 90  | 47 |
| 710 85  | 40 |
| 710 95  | 49 |
| 711 21  | 63 |
| 711 00  | 47 |
| 711 20  | 49 |
| 711 10  | 55 |

| R+M Nr.   | ⊥  |
|-----------|----|
| 710 009   | 33 |
| 710 19    | 49 |
| 710 559   | 36 |
| 710 79    | 49 |
| 710 29    | 48 |
| 711 219 9 | 53 |
| 711 09    | 51 |
| 711 259   | 70 |

| R+M Nr. | ⊥  |
|---------|----|
| 712 05  | 27 |
| 712 10  | 33 |
| 712 20  | 38 |
| 712 40  | 39 |
| 712 30  | 41 |
| 712 50  | 41 |
| 712 70  | 49 |
| 712 55  | 44 |
| 712 60  | 46 |
| 712 80  | 54 |
| 712 90  | 58 |

| R+M Nr. | ⊥  |
|---------|----|
| 713 10  | 21 |
| 713 20  | 26 |
| 713 40  | 26 |
| 713 30  | 28 |
| 713 50  | 33 |
| 713 70  | 37 |
| 713 32  | 30 |
| 713 60  | 32 |
| 713 80  | 36 |

| DN    | ⊙    |
|-------|------|
| 6 mm  | 1/4" |
| 8 mm  | 1/4" |
| 8 mm  | 3/8" |
| 8 mm  | 1/2" |
| 12 mm | 3/8" |
| 12 mm | 1/2" |

| R+M Nr. | ⊥  |
|---------|----|
| 710 104 | 33 |
| 710 204 | 33 |
| 710 504 | 33 |
| 710 704 | 36 |
| 710 604 | 40 |
| 710 804 | 38 |

2/3 Schlauchverschraubungen

Hutsiebeinsatz



Flachdichtung

| R+M Nr. | ⊙    |
|---------|------|
| 725 40  | 3/4" |



Messing.  
Max. 150 °C



Kunststoff.  
Max. 60 °C



Messing.  
Max. 150 °C

| DN    | ⊙    |
|-------|------|
| 10 mm | 1/2" |
| 10 mm | 3/4" |
| 13 mm | 1/2" |
| 13 mm | 3/4" |
| 13 mm | 1"   |
| 19 mm | 3/4" |
| 19 mm | 1"   |
| 25 mm | 1"   |

| R+M Nr. | ⊥  |
|---------|----|
| 711 52  | 34 |
| 711 50  | 36 |
| 711 51  | 41 |
| 711 55  | 39 |
| 711 56  | 38 |
| 711 57  | 40 |

| R+M Nr. | ⊥  |
|---------|----|
| 711 60  | 49 |

| R+M Nr. | ⊥  |
|---------|----|
| 711 68  | 41 |
| 711 75  | 41 |
| 711 70  | 42 |
| 711 77  | 46 |


Schlauchverbinder



Kunststoff.  
Max. 60 °C



Kunststoff.  
Max. 60 °C



Kunststoff.  
Max. 60 °C

| DN    |
|-------|
| 6 mm  |
| 8 mm  |
| 12 mm |

| R+M Nr. | ⊥  |
|---------|----|
| 715 10  | 49 |
| 715 20  | 56 |
| 715 30  | 73 |

| R+M Nr. | ↔  | ⊥  |
|---------|----|----|
| 717 10  | 50 | 26 |
| 717 20  | 58 | 30 |
| 717 30  | 68 | 36 |

| R+M Nr. | ⊥  |
|---------|----|
| 716 10  | 46 |
| 716 20  | 53 |
| 716 30  | 68 |

Symbole DN Nennweite ⊙ Gewinde ⊥ Höhe ↔ Länge VPE Verpackungseinheit ⊗ Durchmesser M Material TYP Typ