

Hose tails

Male thread



Brass.
Max. 150 °C



Stainless steel.
Max. 150 °C



Plastic.
Max. 60 °C



Plastic.
Max. 60 °C

Female thread



Brass.
Max. 150 °C

| DN | ⊘ |
|-------|------|
| 4 mm | 1/8" |
| 6 mm | 1/8" |
| 6 mm | 1/4" |
| 6 mm | 3/8" |
| 6 mm | 1/2" |
| 7 mm | 1/8" |
| 8 mm | 1/4" |
| 8 mm | 3/8" |
| 8 mm | 1/2" |
| 9 mm | 3/8" |
| 9 mm | 1/2" |
| 10 mm | 1/4" |
| 10 mm | 3/8" |
| 12 mm | 1/4" |
| 12 mm | 3/8" |
| 12 mm | 1/2" |
| 12 mm | 3/4" |
| 16 mm | 1/2" |
| 16 mm | 3/4" |
| 19 mm | 1/2" |
| 19 mm | 3/4" |
| 19 mm | 1" |
| 25 mm | 3/4" |
| 25 mm | 1" |

| R+M Nr. | ⊓ |
|---------|----|
| 710 00 | 31 |
| 710 10 | 35 |
| 710 40 | 36 |
| 710 65 | 40 |
| 710 05 | 31 |
| 710 20 | 34 |
| 710 50 | 38 |
| 710 70 | 49 |
| 710 25 | 34 |
| 710 55 | 35 |
| 710 30 | 35 |
| 710 60 | 38 |
| 710 80 | 50 |
| 710 90 | 47 |
| 710 85 | 40 |
| 710 95 | 49 |
| 711 21 | 63 |
| 711 00 | 47 |
| 711 20 | 49 |
| 711 10 | 55 |

| R+M Nr. | ⊓ |
|-----------|----|
| 710 009 | 33 |
| 710 19 | 49 |
| 710 559 | 36 |
| 710 79 | 49 |
| 710 29 | 48 |
| 711 219 9 | 53 |
| 711 09 | 51 |
| 711 259 | 70 |

| R+M Nr. | ⊓ |
|---------|----|
| 712 05 | 27 |
| 712 10 | 33 |
| 712 20 | 38 |
| 712 40 | 39 |
| 712 30 | 41 |
| 712 50 | 41 |
| 712 70 | 49 |
| 712 55 | 44 |
| 712 60 | 46 |
| 712 80 | 54 |
| 712 90 | 58 |

| R+M Nr. | ⊓ |
|---------|----|
| 713 10 | 21 |
| 713 20 | 26 |
| 713 40 | 26 |
| 713 30 | 28 |
| 713 50 | 33 |
| 713 70 | 37 |
| 713 32 | 30 |
| 713 60 | 32 |
| 713 80 | 36 |

| DN | ⊘ |
|-------|------|
| 6 mm | 1/4" |
| 8 mm | 1/4" |
| 8 mm | 3/8" |
| 8 mm | 1/2" |
| 12 mm | 3/8" |
| 12 mm | 1/2" |

| R+M Nr. | ⊓ |
|---------|----|
| 710 104 | 33 |
| 710 204 | 33 |
| 710 504 | 33 |
| 710 704 | 36 |
| 710 604 | 40 |
| 710 804 | 38 |

2/3 hose tails

Filter



Flat seal

| R+M Nr. | ⊘ |
|---------|------|
| 725 40 | 3/4" |



Brass.
Max. 150 °C



Plastic.
Max. 60 °C



Brass.
Max. 150 °C

| DN | ⊘ |
|-------|------|
| 10 mm | 1/2" |
| 10 mm | 3/4" |
| 13 mm | 1/2" |
| 13 mm | 3/4" |
| 13 mm | 1" |
| 19 mm | 3/4" |
| 19 mm | 1" |
| 25 mm | 1" |

| R+M Nr. | ⊓ |
|---------|----|
| 711 52 | 34 |
| 711 50 | 36 |
| 711 51 | 41 |
| 711 55 | 39 |
| 711 56 | 38 |
| 711 57 | 40 |

| R+M Nr. | ⊓ |
|---------|----|
| 711 60 | 49 |

| R+M Nr. | ⊓ |
|---------|----|
| 711 68 | 41 |
| 711 75 | 41 |
| 711 70 | 42 |
| 711 77 | 46 |

Hose connectors



Plastic.
Max. 60 °C



Plastic.
Max. 60 °C



Plastic.
Max. 60 °C

| DN |
|-------|
| 6 mm |
| 8 mm |
| 12 mm |

| R+M Nr. | ⊓ |
|---------|----|
| 715 10 | 49 |
| 715 20 | 56 |
| 715 30 | 73 |

| R+M Nr. | ↔ | ⊓ |
|---------|----|----|
| 717 10 | 50 | 26 |
| 717 20 | 58 | 30 |
| 717 30 | 68 | 36 |

| R+M Nr. | ⊓ |
|---------|----|
| 716 10 | 46 |
| 716 20 | 53 |
| 716 30 | 68 |

Symbols DN nominal diameter ⊘ thread ⊓ height ↔ length VPE packing unit ⊚ diameter M material TYP type