

Lances

ST-001 with vented handle ST-9



Plug KW. Lance with vented handle ST-9 and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|-----------|------------|--------|----------|-----------------|
| 511 405 9 | 1/4" F NPT | 380 mm | 800 mm | stainless steel |
| 511 505 9 | 1/4" F NPT | 380 mm | 1,000 mm | stainless steel |

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|---------|------------|--------|----------|-------------------|
| 511 405 | 1/4" F NPT | 380 mm | 800 mm | zinc-plated steel |
| 511 505 | 1/4" F NPT | 380 mm | 1,000 mm | zinc-plated steel |



Plug KW. Lance with vented handle ST-9 and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|------------|------------|--------|----------|-----------------|
| 511 405 91 | 1/4" F NPT | 380 mm | 800 mm | stainless steel |
| 511 505 91 | 1/4" F NPT | 380 mm | 1,000 mm | stainless steel |

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|-----------|------------|--------|----------|-------------------|
| 511 405 1 | 1/4" F NPT | 380 mm | 800 mm | zinc-plated steel |
| 511 505 1 | 1/4" F NPT | 380 mm | 1,000 mm | zinc-plated steel |



Plug KW. Lance with insulation ST-9, grip and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|-----------|------------|--------|----------|-----------------|
| 511 705 9 | 1/4" F NPT | 760 mm | 1,500 mm | stainless steel |
| 511 905 9 | 1/4" F NPT | 760 mm | 2,000 mm | stainless steel |

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|---------|------------|--------|----------|-------------------|
| 511 705 | 1/4" F NPT | 760 mm | 1,500 mm | zinc-plated steel |
| 511 905 | 1/4" F NPT | 760 mm | 2,000 mm | zinc-plated steel |



Plug KW. Lance with insulation ST-9, grip and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|------------|------------|--------|----------|-----------------|
| 511 705 91 | 1/4" F NPT | 760 mm | 1,500 mm | stainless steel |
| 511 905 91 | 1/4" F NPT | 760 mm | 2,000 mm | stainless steel |

| R+M Nr. | ☉ | ISO | ↔ | (M) |
|-----------|------------|--------|----------|-------------------|
| 511 705 1 | 1/4" F NPT | 760 mm | 1,500 mm | zinc-plated steel |
| 511 905 1 | 1/4" F NPT | 760 mm | 2,000 mm | zinc-plated steel |

Symbols ☉ outlet ↔ length (M) material ISO insulation