

ST-85 Push & Pull lances



- » Variable adjustment of spraying angle from 20 to 140°. Especially designed for cleaning of places which are difficult to access such as container, under vehicles, gutters and roofs.
- » 600 mm version suitable for spray guns with integrated extension
- » Max. 210 bar / 150 °C

Grip for vented handle ST-9



Handle for adjustment and locking. Attachable on both sides

R+M Nr.

200 009 680



Kr IP

M22 M. ST-85 lance with nozzle protector ST-10 without high pressure nozzle. Suitable for guns with integrated extension. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M	R+M Nr.	⊖	↔	⊕	M
200 085 270	1/4" F NPT	600 mm	M22 M	stainless steel	200 085 220	1/4" F NPT	600 mm	M22 M	zinc-plated steel



1/4" F. ST-85 Push & Pull lance with nozzle protector ST-10 without high pressure nozzle. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M	R+M Nr.	⊖	↔	⊕	M
200 085 810	1/4" F NPT	850 mm	1/4" F	stainless steel	200 085 710	1/4" F NPT	850 mm	1/4" F	zinc-plated steel
200 085 800	1/4" F NPT	1,000 mm	1/4" F	stainless steel	200 085 700	1/4" F NPT	1,000 mm	1/4" F	zinc-plated steel
200 085 850	1/4" F NPT	1,500 mm	1/4" F	stainless steel	200 085 750	1/4" F NPT	1,500 mm	1/4" F	zinc-plated steel



Kr A

Plug KW. ST-85 Push & Pull lance with nozzle protector ST-10 without high pressure nozzle. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M	R+M Nr.	⊖	↔	⊕	M
200 085 260	1/4" F NPT	600 mm	plug KW	stainless steel	200 085 210	1/4" F NPT	600 mm	plug KW	zinc-plated steel
200 085 610	1/4" F NPT	850 mm	plug KW	stainless steel	200 085 510	1/4" F NPT	850 mm	plug KW	zinc-plated steel
200 085 600	1/4" F NPT	1,000 mm	plug KW	stainless steel	200 085 500	1/4" F NPT	1,000 mm	plug KW	zinc-plated steel
200 085 650	1/4" F NPT	1,500 mm	plug KW	stainless steel	200 085 550	1/4" F NPT	1,500 mm	plug KW	zinc-plated steel

Symbols ⊕ inlet ⊖ outlet ↔ length M material