



### Gun extensions with handle

1/4" M. Lance with handle and insulation ST-28.2/ST-29.2 Cool & Compact. Max. 400 bar / 150 °C



R+M Nr.		ISO		M
200 028 204	1/4" M	400 mm	430 mm	zinc-plated
200 029 204	1/4" M	400 mm	430 mm	stainless steel



R+M Nr.		ISO		M
200 028 210	1/4" M	400 mm	1,000 mm	zinc-plated
200 029 210	1/4" M	400 mm	1,000 mm	stainless steel

### Insulations for lances

#### Insulations ST-9.9



Insulation 330 mm. Suitable for 1/4" lances. Max. 150 °C

R+M Nr.
200 009 935



Insulation 330 mm. Suitable for 1/4" lances. Max. 150 °C

R+M Nr.
200 009 936



#### Vented handles ST-9





Vented handle 380 mm. Suitable for 1/4" lances. Max. 150 °C

R+M Nr.
200 009 510

### Adapter for lances

		M18 M : TR20 F. K-Lock 8. Brass. Max. 400 bar / 150° C
		<table border="1"> <thead> <tr> <th>R+M Nr.</th> </tr> </thead> <tbody> <tr> <td>565 686</td> </tr> </tbody> </table>
R+M Nr.		
565 686		

Symbols  outlet  insulation  length  material