

Lances with ergonomic swivel screw coupling

Lances with insulation ST-22



M22 F swivel. Lance with insulation ST-22 and nozzle protector without tip. Max. 400 bar / 150 °C

R+M Nr.	spray gun	ISO	↔	M	R+M Nr.	spray gun	ISO	↔	M
514 529 1	standard	410 mm	1,000 mm	stainless steel	514 539 1	servopress	410 mm	1,000 mm	stainless steel

Twin lances with moulded handle



M22 F swivel. Lance with moulded handle, valve ST-54 aside and nozzle protector without tip. Max. 310 bar / 150 °C

R+M Nr.	↻	ISO	↔	M	R+M Nr.	↻	ISO	↔	M
		300 mm	980 mm	zinc-plated steel	517 608 5	nozzle protector	300 mm	980 mm	zinc-plated steel



suitable for standard spray guns

M22 F swivel. ST-85 Push & Pull lance with ergonomic swivel screw coupling suitable for standard spray guns. Max. 210 bar / 150 °C

R+M Nr.	↻	↔	⊕	M	R+M Nr.	↻	↔	⊕	M
200 085 645	nozzle protector	850 mm	M22 F swivel	stainless steel	200 085 745	nozzle protector	850 mm	M22 F swivel	zinc-plated steel
200 085 935	nozzle protector	1,000 mm	M22 F swivel	stainless steel	200 085 925	nozzle protector	1,000 mm	M22 F swivel	zinc-plated steel
200 085 685	nozzle protector	1,500 mm	M22 F swivel	stainless steel	200 085 785	nozzle protector	1,500 mm	M22 F swivel	zinc-plated steel
200 085 687	nozzle protector	2,000 mm	M22 F swivel	stainless steel					



suitable for servopress spray guns

M22 F swivel. ST-85 Push & Pull lance with ergonomic swivel screw coupling suitable for servopress spray guns. Max. 210 bar / 150 °C

R+M Nr.	↻	↔	⊕	M	R+M Nr.	↻	↔	⊕	M
200 085 646	nozzle protector	850 mm	M22 F swivel	stainless steel	200 085 746	nozzle protector	850 mm	M22 F swivel	zinc-plated steel
200 085 936	nozzle protector	1,000 mm	M22 F swivel	stainless steel	200 085 926	nozzle protector	1,000 mm	M22 F swivel	zinc-plated steel
200 085 686	nozzle protector	1,500 mm	M22 F swivel	stainless steel	200 085 786	nozzle protector	1,500 mm	M22 F swivel	zinc-plated steel
200 085 688	nozzle protector	2,000 mm	M22 F swivel	stainless steel					

Lances with vented handle ST-9



M22 F swivel. Lance with ergonomic swivel screw coupling, vented handle ST-9 & grip and nozzle protector (M20x1) without tip. Max. 650 bar / 150 °C

R+M Nr.	↻	↔	⊕	M	R+M Nr.
200 146 550	nozzle protector	700 mm	M22 F swivel	stainless steel	